

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO MICRO PUSH WIRE® CONNECTOR FOR JUNCTION BOXES;  
FOR SOLID CONDUCTORS; 0.8 MM Å; 8-CONDUCTOR; LIGHT GRAY  
HOUSING; LIGHT GRAY COVER; SURROUNDING AIR TEMPERATURE:  
MAX 60Å°C; LIGHT GRAY**

Ratings per: EN 60664;  
Tesiune nominala (II/2): 100; V  
Tensiune nominala de supratensiune (II/2): 1,5; kV  
Curent nominal: 6; A  
Legend (ratings): (II / 2) Å%™ Overvoltage category II / Pollution degree 2;  
Tehnologie conexiune: PUSH WIRE®;  
Tip actionare: Push-in;  
Connectable conductor materials: Copper;  
Conductor diameter: 0,6 ... 0,8 mm;  
Strip length: 5 ... 6 mm / 0.2 ... 0.24 inch;  
Numar total de conexiuni: 8;  
Total number of potentials: 1;  
Numar tipuri de conexiuni: 1;  
Numar nivele: 1;  
Wiring type: Side-entry wiring;  
Latime: 18,4 mm / 0.724 inch;  
Inaltime: 6,8 mm / 0.268 inch;  
Adancime: 10 mm / 0.394 inch;  
Culoare: light gray;  
Fire load: 0,019; MJ  
Greutate: 1,4; g  
Surrounding air temperature (operation): 60 °C;  
Continuous operating temperature: 105 °C;  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4044918502689;  
Customs tariff number: 85369010000;  
Pret: 1,85 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/micro-push-wire-connector-for-junction-boxes-for-solid-conductors-0-8-mm-oe-8-conductor-light-gray-housing-light-gray-cover-surrounding-air-temperature-max-600c-light-gray-144734>