

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410

	<p><b>WAGO THT FEMALE HEADER; 0.6 X 1.0 MM SOLDER PIN; STRAIGHT;                  100% PROTECTED AGAINST MISMATING; PIN SPACING 5 MM; 2-                  POLE; LIGHT GRAY</b></p> <p>Ratings per: IEC/EN 60664-1;                  Tensiune nominala (III/3): 320; V                  Tensiune nominala de supratensiune (III/3): 4; kV                  Tensiune nominala (III/2): 320; V                  Tensiune nominala de supratensiune (III/2): 4; kV                  Tensiune nominala (II/2): 630; V                  Tensiune nominala de supratensiune (II/2): 4; kV                  Curent nominal: 12; A                  Legend (ratings): (III / 2) <math>\hat{=}</math> Overvoltage category III / Pollution degree 2;                  Tensiune nominala UL (Use Group B): 300; V                  Curent nominal UL (Use Group B): 15; A                  Tensiune nominala UL (Use Group D): 300; V                  Curent nominal UL (Use Group D): 10; A                  Certificari: UL 1059;                  Tensiune nominala UL 1977: 600; V                  Curent nominal UL 1977: 15; A                  Tensiune nominala CSA (Use Group B): 300; V                  Curent nominal CSA (Use Group B): 15; A                  Tensiune nominala CSA (Use Group D): 300; V                  Curent nominal CSA (Use Group D): 10; A                  Numar poli: 2;                  Total number of potentials: 2;                  Numar tipuri de conexiuni: 1;                  Numar nivele: 1;                  Distanta intre pini: 5 mm / 0.197 inch;                  Latime: 11.5 mm / 0.453 inch;                  Inaltime: 23.25 mm / 0.915 inch;                  Inaltime de la fata: 18.25 mm / 0.719 inch;                  Adancime: 11.6 mm / 0.457 inch;                  Lungimea pinului de contact: 5; mm                  Solder pin dimensions: 0.6 x 1 mm;                  Diametrul de gaurire cu toleranta: 1.3 (+0.1) mm;                  Tip contact (pluggable connector): Conector mama/priza;                  Connector (connection type): for PCBs;                  Mismatching protection: Yes;                  Mating direction to the PCB: 90; °                  PCB contact: THT;                  Solder pin arrangement: over the entire female connector, in line;                  Number of solder pins per potential: 1;                  Culoare: light gray;                  Material group: I;                  Material izolator: Polyamide 66 (PA 66);                  Flammability class per UL94: V0;                  Contact material: Copper alloy;                  Contact plating: tin-plated;                  Fire load: 0,035; MJ                  Greutate: 2; g                  Temperatura lucru: -60 ... +85 °C;                  Product Group: 3 (Multi Conn. System);                  Tip ambalare: BOX;                  Tara de origine: DE;                  GTIN: 4044918580366;                  Customs tariff number: 85366990990;                  Pret: 6,93 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/tht-female-header-0-6-x-1-0-mm-solder-pin-straight-100-protected-against-mismatching-pin-spacing-5-mm-2-pole-light-gray-145021">https://www.materialelectrice.ro/tht-female-header-0-6-x-1-0-mm-solder-pin-straight-100-protected-against-mismatching-pin-spacing-5-mm-2-pole-light-gray-145021</a></p>
--	--