

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO END MODULE FOR 1-CONDUCTOR FEMALE CONNECTOR; 2.5  
MM<sup>2</sup>; 1-POLE; 2,50 MM<sup>2</sup>; GREEN-YELLOW**

Ratings per: IEC/EN 61984;  
Tehnologie conexiune: Push-in CAGE CLAMP®;  
Tip actionare: Open Tool Slot; Push-in;  
Connectable conductor materials: Copper;  
Nominal cross-section: 2,5 mm<sup>2</sup>;  
Solid conductor: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;  
Solid conductor; push-in termination: 0,75 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;  
Fine-stranded conductor: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;  
Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm<sup>2</sup> / 18 ... 12 AWG;  
Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm<sup>2</sup> / 18 ... 12 AWG;  
Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;  
Numar poli: 1;  
Numar total de conexiuni: 1;  
Total number of potentials: 1;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;  
Latime: 5,2 mm / 0.205 inch;  
Inaltime: 40,5 mm / 1.594 inch;  
Adancime: 22,4 mm / 0.882 inch;  
Marking level: Side marking;  
Tip contact (pluggable connector): Conector mama/priza;  
Connector (connection type): for conductor;  
Culoare: green-yellow;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,053; MJ  
Greutate: 3,2; g  
Product Group: 18 (X-COM-System);  
Tip ambalare: BOX;  
Tara de origine: CN;  
GTIN: 4050821243434;  
Customs tariff number: 85366990990;  
Pret: 4,65 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/end-module-for-1-conductor-female-connector-2-5-mm2-1-pole-2-50-mm2-green-yellow-145109>