

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO PUSH WIRE® CONNECTOR FOR JUNCTION BOXES; FOR  
SOLID AND STRANDED CONDUCTORS; FOR EX APPLICATIONS; MAX.  
2.5 MM<sup>2</sup>; 6-CONDUCTOR; LIGHT GRAY HOUSING; LIGHT GRAY  
COVER; SURROUNDING AIR TEMPERATURE: MAX 60°C; 2,50 MM<sup>2</sup>**

Ratings per: IEC/EN 60664-1;  
Curent nominal: 24; A  
Tensiune nominala EN (Ex e II): 550; V  
Tehnologie conexiune: PUSH WIRE®;  
Tip actionare: Push-in;  
Connectable conductor materials: Copper; Aluminum;  
Solid conductor: 0,75 ... 2,5 mm<sup>2</sup> / 18 ... 14 AWG;  
Strip length: 12 mm / 0.47 inch;  
Numar total de conexiuni: 6;  
Total number of potentials: 1;  
Wiring type: Side-entry wiring;  
Latime: 18,8 mm / 0.74 inch;  
Inaltime: 13,1 mm / 0.516 inch;  
Adancime: 19,5 mm / 0.768 inch;  
Cover Culoare: light gray;  
Flammability class per UL94: V2;  
Fire load: 0,077; MJ  
Greutate: 3,6; g  
Surrounding air temperature (operation): 60 °C;  
Continuous operating temperature: 105 °C;  
Product Group: 7 (Push Wire Conn.);  
Tip ambalare: BOX;  
Tara de origine: CN;  
GTIN: 4055143026581;  
Customs tariff number: 85369010000;  
Pret: 2,45 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/push-wire-connector-for-junction-boxes-for-solid-and-stranded-conductors-for-ex-applications-max-2-5-mm2-6-conductor-light-gray-housing-light-gray-cover-surrounding-air-temperature-max-600c-2-50-mm2-145378>