

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO MICRO PUSH WIRE® CONNECTOR FOR JUNCTION BOXES;
FOR SOLID CONDUCTORS; 0.8 MM $\tilde{\sim}$; 4-CONDUCTOR;
TRANSPARENT HOUSING; LIGHT GRAY COVER; SURROUNDING AIR
TEMPERATURE: MAX 60°C; TRANSPARENT**

Ratings per: EN 60664;
Tesiune nominala (II/2): 100; V
Tensiune nominala de supratensiune (II/2): 1,5; kV
Curent nominal: 6; A
Legend (ratings): (II / 2) $\hat{\%}$ ™ Overvoltage category II / Pollution degree 2;
Tehnologie conexiune: PUSH WIRE®;
Tip actionare: Push-in;
Connectable conductor materials: Copper;
Conductor diameter: 0,4 ... 0,5 mm;
Strip length: 5 ... 6 mm / 0.2 ... 0.24 inch;
Numar total de conexiuni: 4;
Total number of potentials: 1;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Wiring type: Side-entry wiring;
Latime: 10 mm / 0.394 inch;
Inaltime: 6,8 mm / 0.268 inch;
Adancime: 10 mm / 0.394 inch;
Culoare: transparent;
Fire load: 0,011; MJ
Greutate: 0,8; g
Surrounding air temperature (operation): 60 °C;
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918937788;
Customs tariff number: 85369010000;
Pret: 1,13 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/micro-push-wire-connector-for-junction-boxes-for-solid-conductors-0-8-mm-oe-4-conductor-transparent-housing-light-gray-cover-surrounding-air-temperature-max-60c-transparent-145426>