


Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410



**WAGO THT MALE HEADER, 2-ROW; 0.8 X 0.8 MM SOLDER PIN;
 STRAIGHT; 100% PROTECTED AGAINST MISMATING; PIN SPACING
 3.5 MM; 2 X 8-POLE; BLACK**

Ratings per: IEC/EN 60664-1;
 Tensiune nominala (III/3): 80; V
 Tensiune nominala de supratensiune (III/3): 2,5; kV
 Tensiune nominala (III/2): 160; V
 Tensiune nominala de supratensiune (III/2): 2,5; kV
 Tensiune nominala (II/2): 250; V
 Tensiune nominala de supratensiune (II/2): 2,5; kV
 Curent nominal: 10; A
 Legend (ratings): (III / 2) \hat{a} %^o™ Overvoltage category III / Pollution degree 2;
 Tensiune nominala UL (Use Group B): 150; V
 Curent nominal UL (Use Group B): 10; A
 Tensiune nominala UL (Use Group C): 50; V
 Curent nominal UL (Use Group C): 10; A
 Certificari: UL 1059;
 Tensiune nominala CSA (Use Group B): 150; V
 Curent nominal CSA (Use Group B): 12; A
 Numar poli: 16;
 Total number of potentials: 16;
 Numar tipuri de conexiuni: 1;
 Numar nivele: 2;
 Distanta intre pini: 3,5 mm / 0.138 inch;
 Latime: 29,5 mm / 1.161 inch;
 Inaltime: 17,3 mm / 0.681 inch;
 Inaltime de la fata: 13,5 mm / 0.531 inch;
 Adancime: 13,3 mm / 0.524 inch;
 Lungimea pinului de contact: 3,8; mm
 Solder pin dimensions: 0,8 x 0,8 mm;
 Diametrul de gaurire cu toleranta: 1,2 (+0,1) mm;
 Tip contact (pluggable connector): Conector tata/fisa;
 Connector (connection type): for PCBs;
 Mismatching protection: Yes;
 Mating direction to the PCB: 90; °
 PCB contact: THT;
 Solder pin arrangement: over the entire male connector, in line;
 Number of solder pins per potential: 1;
 Culoare: black;
 Material group: I;
 Material izolator: Polyphthalamide (PPA GF);
 Flammability class per UL94: V0;
 Contact material: Cupru electrolitic(ECu);
 Contact plating: tin-plated;
 Fire load: 0,088; MJ
 Greutate: 4,3; g
 Temperatura lucru: -60 ... +100 °C;
 Product Group: 3 (Multi Conn. System);
 Tip ambalare: BOX;
 Tara de origine: PL;
 GTIN: 4045454700034;
 Customs tariff number: 85366990990;
 Pret: 21,19 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tht-male-header-2-row-0-8-x-0-8-mm-solder-pin-straight-100-protected-against-mismatching-pin-spacing-3-5-mm-2-x-8-pole-black-145561>