


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p><u>WAGO THT MALE HEADER, 2-ROW; 0.8 X 0.8 MM SOLDER PIN; STRAIGHT; 100% PROTECTED AGAINST MISMATCHING; THREADED FLANGE; PIN SPACING 3.5 MM; 2 X 18-POLE; BLACK</u></p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 80; V Tensiune nominala de supratensiune (III/3): 2,5; kV Tensiune nominala (III/2): 160; V Tensiune nominala de supratensiune (III/2): 2,5; kV Tensiune nominala (II/2): 250; V Tensiune nominala de supratensiune (II/2): 2,5; kV Curent nominal: 10; A Legend (ratings): (III / 2) % Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 150; V Curent nominal UL (Use Group B): 10; A Tensiune nominala UL (Use Group C): 50; V Curent nominal UL (Use Group C): 10; A Certificari: UL 1059; Tensiune nominala CSA (Use Group B): 150; V Curent nominal CSA (Use Group B): 12; A Numar poli: 36; Total number of potentials: 3; Numar tipuri de conexiuni: 1; Numar nivele: 2; Distanta intre pini: 3.5 mm / 0.138 inch; Latime: 73.1 mm / 2.878 inch; Inaltime: 17.3 mm / 0.681 inch; Inaltime de la fata: 13.5 mm / 0.531 inch; Adancime: 13.3 mm / 0.524 inch; Lungimea pinului de contact: 3,8; mm Solder pin dimensions: 0.8 x 0.8 mm; Diametrul de gaurire cu toleranta: 1.2 (+0.1) mm; Tip contact (pluggable connector): Conector tata/fisa; Connector (connection type): for PCBs; Mismatching protection: Yes; Mating direction to the PCB: 90; ° Locking of plug-in connection: Threaded flange; PCB contact: THT; Solder pin arrangement: over the entire male connector, in line; Number of solder pins per potential: 1; Culoare: black; Material group: I; Material izolator: Polyphthalamide (PPA GF); Flammability class per UL94: V0; Contact material: Cupru electrolitic(ECu); Contact plating: tin-plated; Fire load: 0,192; MJ Greutate: 9,7; g Temperatura lucru: -60 ... +100 °C; Product Group: 3 (Multi Conn. System); Tip ambalare: BOX; Tara de origine: PL; GTIN: 4045454809096; Customs tariff number: 85366990990; Pret: 54,03 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/tht-male-header-2-row-0-8-x-0-8-mm-solder-pin-straight-100-protected-against-mismatching-threaded-flange-pin-spacing-3-5-mm-2-x-18-pole-black-146128</p>
---	--