


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO 2-CONDUCTOR SHIELD TERMINAL BLOCK; 16 MM²;
SUITABLE FOR EX E II APPLICATIONS; SIDE AND CENTER
MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE
CLAMP®; 16,00 MM²; WHITE**

Ratings per: IEC/EN 60947-7-2;
Tensiune nominala CSA (Use Group B): 600; V
Curent nominal CSA (Use Group B): 80; A
Tensiune nominala CSA (Use Group C): 600; V
Curent nominal CSA (Use Group C): 80; A
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Push-in; Open Tool Slot;
Connectable conductor materials: Copper;
Nominal cross-section: 16 mm²;
Solid conductor: 0,5 ... 16 mm² / 20 ... 6 AWG;
Solid conductor; push-in termination: 6 ... 16 mm² / 14 ... 6 AWG;
Fine-stranded conductor: 0,5 ... 25 mm² / 20 ... 4 AWG;
Fine-stranded conductor; with insulated ferrule: 6 ... 16 mm² / 10 ... 6 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 6 ... 16 mm² / 10 ... 6 AWG;
Strip length: 18 ... 20 mm / 0.71 ... 0.79 inch;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;
Number of jumper slots: 2;
Latime: 12 mm / 0.472 inch;
Inaltime from upper-edge of DIN-rail: 36,9 mm / 1.453 inch;
Adancime: 69,8 mm / 2.748 inch;
Design: horizontal type;
Tip montaj: DIN-35 rail;
Marking level: Center/side marking;
Culoare: white;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,28; MJ
Greutate: 36,3; g
Product Group: 22 (TOPJOB S);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4050821193739;
Customs tariff number: 85369010000;
Pret: 32,12 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-shield-terminal-block-16-mm2-suitable-for-ex-e-ii-applications-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-16-00-mm2-white-146930>