

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410

	<p align="center"><b>WAGO THT MALE HEADER, 2-ROW; 0.8 X 0.8 MM SOLDER PIN;                  STRAIGHT; 100% PROTECTED AGAINST MISMATING; PIN SPACING                  3.5 MM; 2 X 7-POLE; BLACK</b></p> <p>Ratings per: IEC/EN 60664-1;                  Tensiune nominala (III/3): 80; V                  Tensiune nominala de supratensiune (III/3): 2,5; kV                  Tensiune nominala (III/2): 160; V                  Tensiune nominala de supratensiune (III/2): 2,5; kV                  Tensiune nominala (II/2): 250; V                  Tensiune nominala de supratensiune (II/2): 2,5; kV                  Curent nominal: 10; A                  Legend (ratings): (III / 2) % Overvoltage category III / Pollution degree 2;                  Tensiune nominala UL (Use Group B): 150; V                  Curent nominal UL (Use Group B): 10; A                  Tensiune nominala UL (Use Group C): 50; V                  Curent nominal UL (Use Group C): 10; A                  Certificari: UL 1059;                  Tensiune nominala CSA (Use Group B): 150; V                  Curent nominal CSA (Use Group B): 12; A                  Numar poli: 14;                  Total number of potentials: 14;                  Numar tipuri de conexiuni: 1;                  Numar nivele: 2;                  Distanta intre pini: 3.5 mm / 0.138 inch;                  Latime: 26 mm / 1.024 inch;                  Inaltime: 17.3 mm / 0.681 inch;                  Inaltime de la fata: 13.5 mm / 0.531 inch;                  Adancime: 13.3 mm / 0.524 inch;                  Lungimea pinului de contact: 3,8; mm                  Solder pin dimensions: 0.8 x 0.8 mm;                  Diametrul de gaurire cu toleranta: 1.2 (+0.1) mm;                  Tip contact (pluggable connector): Conector tata/fisa;                  Connector (connection type): for PCBs;                  Mismatching protection: Yes;                  Mating direction to the PCB: 90; °                  PCB contact: THT;                  Solder pin arrangement: over the entire male connector, in line;                  Number of solder pins per potential: 1;                  Culoare: black;                  Material group: I;                  Material izolator: Polyphthalamide (PPA GF);                  Flammability class per UL94: V0;                  Contact material: Cupru electrolitic(ECu);                  Contact plating: tin-plated;                  Fire load: 0,079; MJ                  Greutate: 3,8; g                  Temperatura lucru: -60 ... +100 °C;                  Product Group: 3 (Multi Conn. System);                  Tip ambalare: BOX;                  Tara de origine: PL;                  GTIN: 4045454700027;                  Customs tariff number: 85366990990;                  Pret: 18,51 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialeelectrice.ro/tht-male-header-2-row-0-8-x-0-8-mm-solder-pin-straight-100-protected-against-mismatching-pin-spacing-3-5-mm-2-x-7-pole-black-146975">https://www.materialeelectrice.ro/tht-male-header-2-row-0-8-x-0-8-mm-solder-pin-straight-100-protected-against-mismatching-pin-spacing-3-5-mm-2-x-7-pole-black-146975</a></p>
--	--