

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p align="center">WAGO THT MALE HEADER, 2-ROW; 0.8 X 0.8 MM SOLDER PIN; ANGLED; 100% PROTECTED AGAINST MISMATING; PIN SPACING 3.5 MM; 2 X 12-POLE; BLACK</p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 80; V Tensiune nominala de supratensiune (III/3): 2,5; kV Tensiune nominala (III/2): 160; V Tensiune nominala de supratensiune (III/2): 2,5; kV Tensiune nominala (II/2): 250; V Tensiune nominala de supratensiune (II/2): 2,5; kV Curent nominal: 10; A Legend (ratings): (III / 2) $\hat{=}$ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 150; V Curent nominal UL (Use Group B): 10; A Tensiune nominala UL (Use Group C): 50; V Curent nominal UL (Use Group C): 10; A Certificari: UL 1059; Tensiune nominala CSA (Use Group B): 150; V Curent nominal CSA (Use Group B): 12; A Numar poli: 24; Total number of potentials: 24; Numar tipuri de conexiuni: 1; Numar nivele: 2; Distanta intre pini: 3,5 mm / 0.138 inch; Latime: 43,5 mm / 1.713 inch; Inaltime: 17,1 mm / 0.673 inch; Inaltime de la fata: 13,3 mm / 0.524 inch; Adancime: 13,5 mm / 0.531 inch; Lungimea pinului de contact: 3,8; mm Solder pin dimensions: 0,8 x 0,8 mm; Diametrul de gaurire cu toleranta: 1,2 (+0,1) mm; Tip contact (pluggable connector): Conector tata/fisa; Connector (connection type): for PCB; Mismating protection: Yes; Mating direction to the PCB: 0; ° PCB contact: THT; Solder pin arrangement: over the entire male connector (in-line); Number of solder pins per potential: 1; Culoare: black; Material group: I; Material izolator: Polyphthalamide (PPA GF); Flammability class per UL94: V0; Contact material: Cupru electrolitic(ECu); Contact plating: tin-plated; Fire load: 0,127; MJ Greutate: 6,5; g Temperatura lucru: -60 ... +100 °C; Product Group: 3 (Multi Conn. System); Tip ambalare: BOX; Tara de origine: PL; GTIN: 4045454700232; Customs tariff number: 85366990990; Pret: 31,65 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/tht-male-header-2-row-0-8-x-0-8-mm-solder-pin-angled-100-protected-against-mismating-pin-spacing-3-5-mm-2-x-12-pole-black-147002</p>
--	--