

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

|  |   |
|--|---|
|  | <p><b><u>WAGO BOARD-TO-BOARD LINK; PIN SPACING 3 MM; 2-POLE;<br/>LENGTH: 15.3 MM; WHITE</u></b></p> <p>Ratings per: IEC/EN 60664-1;<br/>Tensiune nominala (III/3): 63; V<br/>Tensiune nominala de supratensiune (III/3): 2,5; kV<br/>Tensiune nominala (III/2): 160; V<br/>Tensiune nominala de supratensiune (III/2): 2,5; kV<br/>Tensiune nominala (II/2): 320; V<br/>Tensiune nominala de supratensiune (II/2): 2,5; kV<br/>Curent nominal: 3; A<br/>Legend (ratings): (III / 2) % Overvoltage category III / Pollution degree 2;<br/>Certificari: UL 1059;<br/>Numar poli: 2;<br/>Total number of potentials: 2;<br/>Numar tipuri de conexiuni: 1;<br/>Distanta intre pini: 3 mm / 0.118 inch;<br/>Latime: 5,7 mm / 0.224 inch;<br/>Inaltime: 2,5 mm / 0.098 inch;<br/>Adancime: 15,3 mm / 0.602 inch;<br/>Mating cycles (max.): 10;<br/>Number of mating cycles: max. 10 connections/disconnections;<br/>Suitable: for SMD PCB Terminal Blocks; 2059 Series;<br/>Culoare: white;<br/>Material group: I;<br/>Material izolator: Polyamide 66 (PA 66);<br/>Flammability class per UL94: V0;<br/>Contact material: Copper alloy;<br/>Contact plating: silver-plated;<br/>Greutate: 0,1; g<br/>Temperatura lucru: -60 ... +105 °C;<br/>Tip ambalare: BOX;<br/>Tara de origine: CN;<br/>GTIN: 4055143610025;<br/>Customs tariff number: 85369010000;<br/>Pret: 2,21 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialeelectrice.ro/board-to-board-link-pin-spacing-3-mm-2-pole-length-15-3-mm-white-147125">https://www.materialeelectrice.ro/board-to-board-link-pin-spacing-3-mm-2-pole-length-15-3-mm-white-147125</a></p> |
|--|---|