


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO DOUBLE-DECK TERMINAL BLOCK; SHIELD/THROUGH  
TERMINAL BLOCK; SHIELD/L; WITHOUT MARKER CARRIER; FOR  
DIN-RAIL 35 X 15 AND 35 X 7.5; 1 MM<sup>2</sup>; PUSH-IN CAGE CLAMP®;  
1,00 MM<sup>2</sup>; GRAY**

Ratings per: IEC/EN 60947-7-1;  
Tensiune nominala (III/3): 800; V  
Tensiune nominala de supratensiune (III/3): 8; kV  
Curent nominal: 16; A  
Curent nominal 2: 18; A  
Legend (ratings): (III / 3) %<sup>o</sup>™ Overvoltage category III / Pollution degree 3;  
Tensiune nominala UL (Use Group B): 600; V  
Curent nominal UL (Use Group B): 15; A  
Tensiune nominala UL (Use Group C): 600; V  
Curent nominal UL (Use Group C): 15; A  
Certificari: UL 1059;  
Tehnologie conexiune: Push-in CAGE CLAMP®;  
Number of connection points (connection type): 2;  
Tip actionare: Push-in; Open Tool Slot;  
Connectable conductor materials: Copper;  
Nominal cross-section: 1 mm<sup>2</sup>;  
Solid conductor: 0,14 ... 1,5 mm<sup>2</sup> / 24 ... 16 AWG;  
Solid conductor; push-in termination: 0,5 ... 1,5 mm<sup>2</sup> / 20 ... 16 AWG;  
Fine-stranded conductor: 0,14 ... 1,5 mm<sup>2</sup> / 24 ... 16 AWG;  
Fine-stranded conductor; with insulated ferrule: 0,5 ... 0,75 mm<sup>2</sup> / 20 ... 18 AWG;  
Fine-stranded conductor; with ferrule; push-in termination: 0,5 ... 0,75 mm<sup>2</sup> / 20 ... 18 AWG;  
Strip length: 9 ... 11 mm / 0.35 ... 0.43 inch;  
Number of connection points: 2;  
Numar total de conexiuni: 4;  
Total number of potentials: 2;  
Numar nivele: 2;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;  
Latime: 4,2 mm / 0.165 inch;  
Inaltime from upper-edge of DIN-rail: 51,7 mm / 2.035 inch;  
Adancime: 69,7 mm / 2.744 inch;  
Design: horizontal type;  
Tip montaj: DIN-35 rail;  
Potential marking: Schirm/L;  
Marking level: Center/side marking;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,204; MJ  
Greutate: 11,5; g  
Product Group: 22 (TOPJOB S);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4050821037644;  
Customs tariff number: 85369010000;  
Pret: 25,73 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/double-deck-terminal-block-shield-through-terminal-block-shield-l-without-marker-carrier-for-din-rail-35-x-15-and-35-x-7-5-1-mm2-push-in-cage-clamp-1-00-mm2-gray-150287>