

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p align="center">WAGO 1-CONDUCTOR FEMALE PLUG; 100% PROTECTED AGAINST MISMATING; SNAP-IN MOUNTING FEET; 1.5 MM²; PIN SPACING 3.5 MM; 4-POLE; 1,50 MM²; LIGHT GRAY</p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 160; V Tensiune nominala de supratensiune (III/3): 2,5; kV Tensiune nominala (III/2): 160; V Tensiune nominala de supratensiune (III/2): 2,5; kV Tensiune nominala (II/2): 320; V Tensiune nominala de supratensiune (II/2): 2,5; kV Curent nominal: 10; A Legend (ratings): (III / 2) %TM Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 10; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Tensiune nominala CSA (Use Group B): 300; V Curent nominal CSA (Use Group B): 10; A Tensiune nominala CSA (Use Group D): 300; V Curent nominal CSA (Use Group D): 10; A Tehnologie conexiune: CAGE CLAMP®; Tip actionare: Operating tool; Solid conductor: 0.08 ... 1.5 mm² / 28 ... 14 AWG; Fine-stranded conductor: 0.08 ... 1.5 mm² / 28 ... 14 AWG; Fine-stranded conductor; with insulated ferrule: 0.25 ... 1.5 mm²; Fine-stranded conductor; with uninsulated ferrule: 0.25 ... 1.5 mm²; Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch; Numar poli: 4; Numar total de conexiuni: 4; Total number of potentials: 4; Numar tipuri de conexiuni: 1; Numar nivele: 1; Note (conductor cross-section): Terminating 1.5 mm² conductors is possible; however insulation diameter does not allow clamping units to be terminated in a row.; Conductor entry direction to mating direction: 0; ° Distanta intre pini: 3.5 mm / 0.138 inch; Latime: 16.2 mm / 0.638 inch; Inaltime: 18.9 mm / 0.744 inch; Inaltime de la fata: 13.4 mm / 0.528 inch; Adancime: 18.6 mm / 0.732 inch; Housing sheet thickness: 0.6 ... 1.2 mm / 0.024 ... 0.047 inch; Tip montaj: Snap-in mounting foot; Tip montaj: Panel mounting; Tip contact (pluggable connector): Conector mama/priza; Connector (connection type): for conductors; Mismating protection: Yes; Culoare: light gray; Material group: I; Material izolator: Polyamide 66 (PA 66); Flammability class per UL94: V0; Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Copper alloy; Contact plating: tin-plated; Fire load: 0,055; MJ Greutate: 3,2; g Temperatura lucru: -60 ... +100 °C; Product Group: 3 (Multi Conn. System); Tip ambalare: BOX; Tara de origine: DE; GTIN: 4045454930677; Customs tariff number: 85366990990; Pret: 15,23 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/1-conductor-female-plug-100-protected-against-mismating-snap-in-mounting-feet-1-5-mm2-pin-spacing-3-5-mm-4-pole-1-50-mm2-light-gray-150341</p>
--	---