


Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410



**WAGO THR MALE HEADER; 1.0 MM $\tilde{\sim}$ SOLDER PIN; STRAIGHT; PIN
 SPACING 3.5 MM; 2-POLE; LIGHT GRAY**

Ratings per: IEC/EN 60664-1;
 Tensiune nominala (III/3): 160; V
 Tensiune nominala de supratensiune (III/3): 2,5; kV
 Tensiune nominala (III/2): 160; V
 Tensiune nominala de supratensiune (III/2): 2,5; kV
 Tensiune nominala (II/2): 320; V
 Tensiune nominala de supratensiune (II/2): 2,5; kV
 Curent nominal: 10; A
 Legend (ratings): (III / 2) $\hat{\sim}$ ™ Overvoltage category III / Pollution degree 2;
 Tensiune nominala UL (Use Group B): 300; V
 Curent nominal UL (Use Group B): 10; A
 Tensiune nominala UL (Use Group D): 300; V
 Curent nominal UL (Use Group D): 10; A
 Certificari: UL 1059;
 Numar poli: 2;
 Total number of potentials: 2;
 Numar tipuri de conexiuni: 1;
 Numar nivele: 1;
 Distanta intre pini: 3,5 mm / 0.138 inch;
 Latime: 9 mm / 0.354 inch;
 Inaltime: 19,9 mm / 0.783 inch;
 Inaltime de la fata: 17,5 mm / 0.689 inch;
 Adancime: 12,4 mm / 0.488 inch;
 Lungimea pinului de contact: 2,4; mm
 Diametrul pinului de contact: 1; mm
 Diametru placat prin gaura (THR): 1,2 (+0,1) mm;
 Tip contact (pluggable connector): Conector tata/fisa;
 Connector (connection type): for PCB;
 Mismatching protection: No;
 Mating direction to the PCB: 90; °
 Locking of plug-in connection: Locking latch;
 PCB contact: THR;
 Culoare: light gray;
 Material group: I;
 Material izolator: Polyphthalamide (PPA GF);
 Flammability class per UL94: V0;
 Contact material: Cupru electrolitic(ECu);
 Contact plating: tin-plated;
 Fire load: 0,022; MJ
 Greutate: 0,9; g
 Temperatura lucru: -60 ... +100 °C;
 Tip ambalare: BOX;
 Tara de origine: DE;
 GTIN: 4050821396093;
 Customs tariff number: 85366990990;
 Pret: 2,45 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/thr-male-header-1-0-mm-oe-solder-pin-straight-pin-spacing-3-5-mm-2-pole-light-gray-150386>