


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

|   |   |
|---|---|
|  | <p><b><u>WAGO DOUBLE-DECK TERMINAL BLOCK; THROUGH/THROUGH TERMINAL BLOCK; WITH END PLATE; L/L; WITH MARKER CARRIER; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM<sup>2</sup>; PUSH-IN CAGE CLAMP<sup>®</sup>; 2,50 MM<sup>2</sup>; GRAY</u></b></p> <p>Ratings per: IEC/EN 60947-7-1;<br/>Tensiune nominala (III/3): 800; V<br/>Tensiune nominala de supratensiune (III/3): 8; kV<br/>Curent nominal: 24; A<br/>Legend (ratings): (III / 3) <sup>â%</sup>™ Overvoltage category III / Pollution degree 3;<br/>Tensiune nominala UL (Use Group B): 600; V<br/>Curent nominal UL (Use Group B): 15; A<br/>Tensiune nominala UL (Use Group C): 600; V<br/>Curent nominal UL (Use Group C): 15; A<br/>Tensiune nominala UL (Use Group D): 600; V<br/>Curent nominal UL (Use Group D): 5; A<br/>Certificari: UL 1059;<br/>Tehnologie conexiune: Push-in CAGE CLAMP<sup>®</sup>;<br/>Number of connection points (connection type): 2;<br/>Tip actionare: Push-in; Open Tool Slot;<br/>Connectable conductor materials: Copper;<br/>Nominal cross-section: 2,5 mm<sup>2</sup>;<br/>Solid conductor: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;<br/>Solid conductor; push-in termination: 0,75 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;<br/>Fine-stranded conductor: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;<br/>Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm<sup>2</sup> / 18 ... 12 AWG;<br/>Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm<sup>2</sup> / 18 ... 12 AWG;<br/>Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;<br/>Number of connection points: 2;<br/>Numar total de conexiuni: 4;<br/>Total number of potentials: 2;<br/>Numar nivele: 2;<br/>Wiring type: Front-entry wiring;<br/>Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;<br/>Latime: 6,2 mm / 0.244 inch;<br/>Inaltime from upper-edge of DIN-rail: 61,8 mm / 2.433 inch;<br/>Adancime: 69,7 mm / 2.744 inch;<br/>Design: horizontal type;<br/>Tip montaj: DIN-35 rail;<br/>Potential marking: L/L;<br/>Marking level: Center/side marking;<br/>Culoare: gray;<br/>Material izolator: Polyamide 66 (PA 66);<br/>Fire load: 0,31; MJ<br/>Greutate: 13,7; g<br/>Tip ambalare: BOX;<br/>Tara de origine: DE;<br/>GTIN: 4050821299059;<br/>Customs tariff number: 85369010000;<br/>Pret: 14,55 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/double-deck-terminal-block-through-through-terminal-block-with-end-plate-l-l-with-marker-carrier-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2-50-mm2-gray-150620">https://www.materialelectrice.ro/double-deck-terminal-block-through-through-terminal-block-with-end-plate-l-l-with-marker-carrier-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2-50-mm2-gray-150620</a></p> |
|---|---|