

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410

**WAGO THR PCB TERMINAL BLOCK; PUSH-BUTTON; 1.5 MM<sup>2</sup>; PIN SPACING 3.5 MM; 4-POLE; PUSH-IN CAGE CLAMP®; 1.50 MM<sup>2</sup>; BLACK**

Ratings per: IEC/EN 60664-1;  
 Tensiune nominala (III/3): 200; V  
 Tensiune nominala de supratensiune (III/3): 4; kV  
 Tensiune nominala (III/2): 320; V  
 Tensiune nominala de supratensiune (III/2): 4; kV  
 Tensiune nominala (II/2): 320; V  
 Tensiune nominala de supratensiune (II/2): 4; kV  
 Curent nominal: 8; A  
 Legend (ratings): (III / 2) % Overvoltage category III / Pollution degree 2;  
 Tensiune nominala UL (Use Group B): 300; V  
 Curent nominal UL (Use Group B): 8; A  
 Tensiune nominala UL (Use Group D): 300; V  
 Curent nominal UL (Use Group D): 5; A  
 Certificari: UL 1059;  
 Tensiune nominala CSA (Use Group B): 300; V  
 Curent nominal CSA (Use Group B): 10; A  
 Tensiune nominala CSA (Use Group D): 300; V  
 Curent nominal CSA (Use Group D): 10; A  
 Tehnologie conexiune: Push-in CAGE CLAMP®;  
 Tip actionare: Push-button;  
 Solid conductor: 0,2 ... 1,5 mm<sup>2</sup> / 24 ... 16 AWG;  
 Fine-stranded conductor: 0,2 ... 1,5 mm<sup>2</sup> / 24 ... 16 AWG;  
 Fine-stranded conductor; with insulated ferrule: 0,25 ... 1 mm<sup>2</sup>;  
 Fine-stranded conductor; with uninsulated ferrule: 0,25 ... 1 mm<sup>2</sup>;  
 Strip length: 8,5 ... 9,5 mm / 0.33 ... 0.37 inch;  
 Conductor connection direction to PCB: 45; °  
 Numar poli: 4;  
 Numar total de conexiuni: 4;  
 Total number of potentials: 4;  
 Numar tipuri de conexiuni: 1;  
 Numar nivele: 1;  
 Distanta intre pini: 3,5 mm / 0.138 inch;  
 Latime: 15,5 mm / 0.61 inch;  
 Inaltime: 15,5 mm / 0.61 inch;  
 Inaltime de la fata: 13,1 mm / 0.516 inch;  
 Adancime: 12 mm / 0.472 inch;  
 Lungimea pinului de contact: 2,4; mm  
 Solder pin dimensions: 0,4 x 0,75 mm;  
 Diametru placat prin gaura (THR): 1 (+0,1) mm;  
 PCB contact: THR;  
 Solder pin arrangement: over the entire terminal strip (staggered);  
 Number of solder pins per potential: 1;  
 Culoare: black;  
 Material group: III a;  
 Material izolator: Polyamide 46 (PA 46);  
 Flammability class per UL94: V2;  
 Clamping spring material: Copper alloy;  
 Contact material: Cupru electrolitic(ECu);  
 Contact plating: tin-plated;  
 Fire load: 0,046; MJ  
 Greutate: 2,1; g  
 Temperatura lucru: -60 ... +115 °C;  
 Product Group: 4 (Printed Circuit);  
 Tip ambalare: BOX;  
 Tara de origine: CH;  
 GTIN: 4045454915940;  
 Customs tariff number: 85369010000;  
 Pret: 5,25 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/thr-pcb-terminal-block-push-button-1-5-mm2-pin-spacing-3-5-mm-4-pole-push-in-cage-clamp-1-50-mm2-black-150777>