

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO DOUBLE-DECK TERMINAL BLOCK; ORANGE SEPARATOR; L;
OVERSIZED; CONTACT INSERTS ONLY ON UPPER DECK; FOR DIN-
RAIL 35 X 15 AND 35 X 7.5; 2,5 MM²; PUSH-IN CAGE CLAMP®;
2,50 MM²; GRAY**

Voltage type 1: AC/DC;
Voltage type 2: DC;
Ratings per: IEC/EN 60947-7-1;
Tensiune nominala (III/3): 1000; V
Tensiune nominala de supratensiune (III/3): 12; kV
Curent nominal: 24; A
Tensiune nominala (III/3) 2: 1500; V
Tensiune nominala de supratensiune (III/3) 2: 12; kV
Legend (ratings): (III / 3) %TM Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Push-in; Open Tool Slot;
Connectable conductor materials: Copper;
Nominal cross-section: 2,5 mm²;
Solid conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;
Solid conductor; push-in termination: 0,75 ... 4 mm² / 18 ... 12 AWG;
Fine-stranded conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;
Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm² / 18 ... 12 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm² / 18 ... 12 AWG;
Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar nivele: 2;
Wiring type: Front-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;
Latime: 7,2 mm / 0.283 inch;
Inaltime from upper-edge of DIN-rail: 53,3 mm / 2.098 inch;
Adancime: 69,9 mm / 2.752 inch;
Design: horizontal type;
Tip montaj: DIN-35 rail;
Potential marking: L;
Marking level: Center/side marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Greutate: 13,2; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143420235;
Customs tariff number: 85369010000;
Pret: 22,57 lei (TVA inclus)

Detalii online: <https://www.materialeelectriche.ro/double-deck-terminal-block-orange-separator-l-oversized-contact-inserts-only-on-upper-deck-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2-50-mm2-gray-150800>