

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410

	<p><b><u>WAGO THT MALE HEADER, 2-ROW; 0.8 X 0.8 MM SOLDER PIN; ANGLED; 100% PROTECTED AGAINST MISMATING; THREADED FLANGE; PIN SPACING 3.5 MM; 2 X 7-POLE; BLACK</u></b></p> <p>Ratings per: IEC/EN 60664-1;          Tensiune nominala (III/3): 80; V          Tensiune nominala de supratensiune (III/3): 2,5; kV          Tensiune nominala (III/2): 160; V          Tensiune nominala de supratensiune (III/2): 2,5; kV          Tensiune nominala (II/2): 250; V          Tensiune nominala de supratensiune (II/2): 2,5; kV          Curent nominal: 10; A          Legend (ratings): (III / 2) <math>\hat{=}</math> Overvoltage category III / Pollution degree 2;          Tensiune nominala UL (Use Group B): 150; V          Curent nominal UL (Use Group B): 10; A          Tensiune nominala UL (Use Group C): 50; V          Curent nominal UL (Use Group C): 10; A          Certificari: UL 1059;          Tensiune nominala CSA (Use Group B): 150; V          Curent nominal CSA (Use Group B): 12; A          Numar poli: 14;          Total number of potentials: 14;          Numar tipuri de conexiuni: 1;          Numar nivele: 2;          Distanta intre pini: 3.5 mm / 0.138 inch;          Latime: 34.6 mm / 1.362 inch;          Inaltime: 17.1 mm / 0.673 inch;          Inaltime de la fata: 13.3 mm / 0.524 inch;          Adancime: 13.5 mm / 0.531 inch;          Lungimea pinului de contact: 3,8; mm          Solder pin dimensions: 0.8 x 0.8 mm;          Diametrul de gaurire cu toleranta: 1.2 (+0.1) mm;          Tip contact (pluggable connector): Conector tata/fisa;          Connector (connection type): for PCBs;          Mismatching protection: Yes;          Mating direction to the PCB: 0; °          Locking of plug-in connection: Threaded flange;          PCB contact: THT;          Solder pin arrangement: over the entire male connector, in line;          Number of solder pins per potential: 1;          Culoare: black;          Material group: I;          Material izolator: Polyphthalamide (PPA GF);          Flammability class per UL94: V0;          Contact material: Cupru electrolitic(ECu);          Contact plating: tin-plated;          Fire load: 0,086; MJ          Greutate: 4,5; g          Temperatura lucru: -60 ... +100 °C;          Product Group: 3 (Multi Conn. System);          Tip ambalare: BOX;          Tara de origine: PL;          GTIN: 4045454809140;          Customs tariff number: 85366990990;          Pret: 25,20 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/tht-male-header-2-row-0-8-x-0-8-mm-solder-pin-angled-100-protected-against-mismatching-threaded-flange-pin-spacing-3-5-mm-2-x-7-pole-black-150820">https://www.materialelectrice.ro/tht-male-header-2-row-0-8-x-0-8-mm-solder-pin-angled-100-protected-against-mismatching-threaded-flange-pin-spacing-3-5-mm-2-x-7-pole-black-150820</a></p>
--	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------