


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 2.5 MM<sup>2</sup>; SIDE  
AND CENTER MARKING; FOR DIN-15 RAIL; CAGE CLAMP®; 2,50  
MM<sup>2</sup>; ORANGE**

Ratings per: IEC/EN 60947-7-1;  
Tensiune nominala (III/3): 500; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Curent nominal: 24; A  
Legend (ratings): (III / 3) %™ Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 0,08 ... 2,5 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;  
Numar total de conexiuni: 2;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Latime: 5 mm / 0.197 inch;  
Inaltime from upper-edge of DIN-rail: 26,5 mm / 1.043 inch;  
Adancime: 34,5 mm / 1.358 inch;  
Design: horizontal type;  
Tip montaj: DIN-15 rail;  
Marking level: Side marking;  
Culoare: orange;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,07; MJ  
Greutate: 4; g  
Product Group: 16 (Rail Mounted Terminal Block with CCC);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4044918478489;  
Customs tariff number: 85369010000;  
Pret: 4,83 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-through-terminal-block-2-5-mm2-side-and-center-marking-for-din-15-rail-cage-clamp-2-50-mm2-orange-150841>