


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;">WAGO PRE-ASSEMBLED INTERCONNECTING CABLE; SOCKET/SCHUKO PLUG; 3-POLE; COD. A; H05VV-F 3G 2.5 MM²; 2 M; 2,50 MM²; BLACK</p> <p>Note on Contact Resistance: approx. 1 mΩ; of contact resistanceâ€© approx. 0.25 mΩ; contact transition plug/socket; Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 250; V Tensiune nominala de supratensiune (III/3): 4; kV Curent nominal: 20; A Legend (ratings): (III / 3) %™ Overvoltage category III / Pollution degree 3; Tensiune nominala UL 1977: 600; V Curent nominal UL 1977: 23; A Numar poli: 3; Total number of potentials: 3; Ground function: with preceding ground contact; Conductor preparation: tip-bonded; Sheathed cable diameter: 9,2 ... 11,4 mm; Sectiunea transversala a firului: 2,5; mm² Distanta intre pini: 10 mm / 0.394 inch; Total length: 2; m Coding: A; Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number); Retention force of a plug-in connection: when locked: > 80N; Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number); Number of mating cycles: 200 (without resistive load) 100 (with resistive load IN = 25 A), tested (4 mm²); Type of pre-assembled cable: Interconnecting cable; Cable type: H05VV-F 3G2.5; Marking: L âš N; Protection type: IP20; Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas.); Potential marking: L âš N; Application: Network application; Mismating protection: Yes; Locking of plug-in connection: locking lever; Locking lever: retrofittable; Culoare: black; Material izolator: Polyamide 66 (PA 66); Fire class per EN 50575: Eca; Contact material: Copper or copper alloy (surface-treated); Connector Culoare: black; Printing color of mating face: white; Strain relief Culoare: black; Printing color of strain relief: white; Sheathed cable Culoare: black; Printing color of sheathed cable: white; Sheath material: PVC; Greutate: 374,7; g Processing temperature: -5 ... +40 °C; Continuous operating temperature: -35 ... +85 °C; Note on continuous operating temperature: PVC cable for temperatures ≤ 70 °C (including halogen-free) Insulating parts for temperatures ≤ 105 °C; Tip ambalare: not packed; Tara de origine: DE; GTIN: 4050821260929; Customs tariff number: 85444290900; Pret: 50,51 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/pre-assembled-interconnecting-cable-socket-schuko-plug-3-pole-cod-a-h05vv-f-3g-2-5-mm2-2-m-2-50-mm2-black-150934</p>
-----------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------