

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

	<p><b>WAGO THR PCB TERMINAL BLOCK; PUSH-BUTTON; 0.75 MM<sup>2</sup>; PIN SPACING 4 MM; 2-POLE; PUSH-IN CAGE CLAMP<sup>®</sup>; IN TAPE-AND-REEL PACKAGING; 0.75 MM<sup>2</sup>; BLACK</b></p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 63; V Tensiune nominala de supratensiune (III/3): 2,5; kV Tensiune nominala (III/2): 160; V Tensiune nominala de supratensiune (III/2): 2,5; kV Tensiune nominala (II/2): 320; V Tensiune nominala de supratensiune (II/2): 2,5; kV Curent nominal: 9; A Legend (ratings): (III / 2) <math>\hat{\%}</math>™ Overvoltage category III / Pollution degree 2; Certificari: UL 1059; Tensiune nominala UL 1977: 320; V Curent nominal UL 1977: 9; A Tehnologie conexiune: Push-in CAGE CLAMP<sup>®</sup>; Tip actionare: Push-button; Solid conductor: 0.2 ... 0.75 mm<sup>2</sup> / 24 ... 18 AWG; Fine-stranded conductor: 0.2 ... 0.75 mm<sup>2</sup> / 24 ... 18 AWG; Fine-stranded conductor; with insulated ferrule: 0.25 ... 0.34 mm<sup>2</sup>; Fine-stranded conductor; with uninsulated ferrule: 0.25 ... 0.34 mm<sup>2</sup>; Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch; Conductor connection direction to PCB: 0; ° Numar poli: 2; Numar total de conexiuni: 2; Total number of potentials: 2; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 4 mm / 0.157 inch; Latime: 7.9 mm / 0.311 inch; Inaltime: 6.9 mm / 0.272 inch; Inaltime de la fata: 4.5 mm / 0.177 inch; Adancime: 12.7 mm / 0.5 inch; Lungimea pinului de contact: 2,4; mm Solder pin dimensions: 1.2 x 0.75 mm; Diametru placat prin gaura (THR): 1.5 (+0.1) mm; Reel diameter of tape-and-reel packaging: 330; mm Tape Latime: 24; mm PCB contact: THR; Solder pin arrangement: over the entire terminal strip, in line; Number of solder pins per potential: 2; Culoare: black; Material group: I; Material izolator: Polyphthalamide (PPA GF); Flammability class per UL94: V0; Clamping spring material: Chrome nickel spring steel (CrNi); Contact material: Copper alloy; Contact plating: tin-plated; Greutate: 0,5; g Temperatura lucru: -60 ... +105 °C; Tip ambalare: BOX; Tara de origine: CH; GTIN: 4055143331210; Customs tariff number: 85369010000; Pret: 3,70 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/thr-pcb-terminal-block-push-button-0-75-mm2-pin-spacing-4-mm-2-pole-push-in-cage-clamp-in-tape-and-reel-packaging-0-75-mm2-black-151120">https://www.materialelectrice.ro/thr-pcb-terminal-block-push-button-0-75-mm2-pin-spacing-4-mm-2-pole-push-in-cage-clamp-in-tape-and-reel-packaging-0-75-mm2-black-151120</a></p>
--	--