

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO PRE-ASSEMBLED CONNECTING CABLE; ECA; PLUG/OPEN-  
ENDED; 3-POLE; COD. S; 5 M; 1,50 MM<sup>2</sup>; BROWN**

Note on Contact Resistance: approx. 1 mΩ; | of contact resistance ≈ 0.25 mΩ; |  
contact transition plug/socket;  
Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/3): 250; V  
Tensiune nominala de supratensiune (III/3): 4; kV  
Curent nominal: 16; A  
Legend (ratings): (III / 3) %™ Overvoltage category III / Pollution degree 3;  
Tensiune nominala UL 1977: 600; V  
Curent nominal UL 1977: 23; A  
Strip length: 11 mm / 0.43 inch;  
Numar poli: 3;  
Total number of potentials: 3;  
Conductor preparation: tip-bonded;  
Sheathed cable diameter: 7,4 ... 9,4 mm;  
Sectiunea transversala a firului: 1,5; mm<sup>2</sup>  
Strip length (outer insulation): 100; mm  
Connection type: Plug - Free end;  
Distanta intre pini: 10 mm / 0.394 inch;  
Total length: 5; m  
Coding: S;  
Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);  
Retention force of a plug-in connection: when locked: > 80N;  
Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending  
on pole number);  
Number of mating cycles: 200 (without resistive load) 100 (with resistive load IN = 25  
A), tested (4 mm<sup>2</sup>);  
Connection type: Plug - free end;  
Type of pre-assembled cable: Connecting cable;  
Cable type: H05Z1Z1-F 3x1.5;  
Marking: 1 2 L;  
Protection type: IP20;  
Note on protection type: Only when mated (these compact connectors are not designed  
for use in open, easily accessible areas.);  
Potential marking: 1 2 L;  
Application: Switching function;  
Suitable: for distribution connectors; series and two-way circuits;  
Mismating protection: Yes;  
Locking of plug-in connection: locking lever;  
Locking lever: retrofittable;  
Culoare: brown;  
Material izolator: Polyamide 66 (PA 66);  
Fire class per EN 50575: Eca;  
Contact material: Copper or copper alloy (surface-treated);  
Fire load: 149,265; MJ  
Connector Culoare: brown;  
Printing color of mating face: white;  
Strain relief Culoare: black;  
Printing color of strain relief: white;  
Sheathed cable Culoare: black;  
Printing color of sheathed cable: white;  
Halogen-free: Yes;  
Greutate: 497,4; g  
Processing temperature: -5 ... +40 °C;  
Continuous operating temperature: -35 ... +85 °C;  
Note on continuous operating temperature: PVC cable for temperatures ≤ 70 °C  
(including halogen-free) Insulating parts for temperatures ≤ 105 °C;  
Tip ambalare: not packed;  
Tara de origine: DE;  
GTIN: 4050821311027;  
Customs tariff number: 85444290900;  
Pret: 54,40 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/pre-assembled-connecting-cable-eca-plug-open-ended-3-pole-cod-s-5-m-1-50-mm2-brown-151122>