

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410

	<p align="center">WAGO THT MALE HEADER; 1.4 MM ~ SOLDER PIN; ANGLED; PIN SPACING 7.5 MM; 3-POLE; LIGHT GRAY</p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 400; V Tensiune nominala de supratensiune (III/3): 6; kV Tensiune nominala (III/2): 630; V Tensiune nominala de supratensiune (III/2): 6; kV Tensiune nominala (II/2): 1000; V Tensiune nominala de supratensiune (II/2): 6; kV Curent nominal: 16; A Legend (ratings): (III / 2) %™ Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 15; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Numar poli: 3; Total number of potentials: 3; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 7,5 mm / 0.295 inch; Latime: 22,2 mm / 0.874 inch; Inaltime: 18 mm / 0.709 inch; Inaltime de la fata: 14,4 mm / 0.567 inch; Adancime: 19,5 mm / 0.768 inch; Lungimea pinului de contact: 3,6; mm Diametrul pinului de contact: 1,4; mm Diametrul de gaurire cu toleranta: 1,6 (+0,1) mm; Tip contact (pluggable connector): Conector tata/fisa; Connector (connection type): for PCB; Mismatching protection: No; Mating direction to the PCB: 0; ° Locking of plug-in connection: Locking latch; PCB contact: THT; Culoare: light gray; Material group: I; Material izolator: Polyphthalamide (PPA GF); Flammability class per UL94: V0; Contact material: Cupru electrolitic(ECu); Contact plating: tin-plated; Fire load: 0,053; MJ Greutate: 2,5; g Temperatura lucru: -60 ... +100 °C; Product Group: 26 (picoMAX); Tip ambalare: BOX; Tara de origine: DE; GTIN: 4050821164685; Customs tariff number: 85366990990; Pret: 5,01 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/tht-male-header-1-4-mm-oe-solder-pin-angled-pin-spacing-7-5-mm-3-pole-light-gray-151176</p>
--	---