

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 6 MM²; WITH TOUCH-PROOF TEST SOCKET; FOR 4 MM \tilde{A} TEST PLUGS; SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE CLAMP®; 6.00 MM²; BLUE

Tensiune nominala (III/3): 500; V
Tensiune nominala de supratensiune (III/3): 6; kV
Curent nominal: 30; A
Legend (ratings): (III / 3) \hat{A} %™ Overvoltage category III / Pollution degree 3;
Tensiune nominala UL (Use Group B): 300; V
Curent nominal UL (Use Group B): 30; A
Tensiune nominala UL (Use Group C): 300; V
Curent nominal UL (Use Group C): 30; A
Tensiune nominala UL (Use Group D): 300; V
Curent nominal UL (Use Group D): 10; A
Certificari: UL 1059;
Tensiune nominala CSA (Use Group B): 300; V
Curent nominal CSA (Use Group B): 30; A
Tensiune nominala CSA (Use Group C): 300; V
Curent nominal CSA (Use Group C): 30; A
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Push-in; Open Tool Slot;
Connectable conductor materials: Copper;
Nominal cross-section: 6 mm²;
Solid conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;
Solid conductor; push-in termination: 1 ... 10 mm² / 14 ... 8 AWG;
Fine-stranded conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;
Fine-stranded conductor; with insulated ferrule: 2,5 ... 6 mm² / 16 ... 10 AWG;
Fine-stranded conductor; with uninsulated ferrule: 1,5 ... 6 mm² / 16 ... 10 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 2,5 ... 6 mm² / 16 ... 17 AWG;
Strip length: 13 ... 15 mm / 0.51 ... 0.59 inch;
Numar total de conexiuni: 2;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Number of jumper slots: 2;
Latime: 8 mm / 0.315 inch;
Inaltime from upper-edge of DIN-rail: 46,8 mm / 1.843 inch;
Adancime: 99,6 mm / 3.921 inch;
Design: angled;
Tip montaj: DIN-35 rail;
Marking level: Center/side marking;
Culoare: blue;
Material izolator: Polyamide 66 (PA 66);
Greutate: 21,9; g
Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4055143300285;
Customs tariff number: 85369010000;
Pret: 36,41 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-through-terminal-block-6-mm2-with-touch-proof-test-socket-for-4-mm-oe-test-plugs-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-6-00-mm2-blue-151200>