


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO 2-CONDUCTOR MODULAR PCB CONNECTOR; FOR SOLDER
PIN STRIP; PUSH-BUTTON; 0.8 MM \hat{A} ; PIN SPACING 3.5 MM; 5-
POLE; 0,50 MM \hat{A} ²; GRAY**

Ratings per: IEC/EN 60664-1;
Tensiune nominala (III/3): 320; V
Tensiune nominala de supratensiune (III/3): 4; kV
Tensiune nominala (III/2): 320; V
Tensiune nominala de supratensiune (III/2): 4; kV
Tensiune nominala (II/2): 630; V
Tensiune nominala de supratensiune (II/2): 4; kV
Curent nominal: 2; A
Legend (ratings): (III / 2) \hat{A} %TM Overvoltage category III / Pollution degree 2;
Tensiune nominala UL (Use Group B): 300; V
Curent nominal UL (Use Group B): 2; A
Tensiune nominala UL (Use Group D): 300; V
Curent nominal UL (Use Group D): 2; A
Certificari: UL 1059;
Tehnologie conexiune: PUSH WIRE®;
Tip actionare: Push-button;
Solid conductor: 0,14 ... 0,5 mm² / 26 ... 20 AWG;
Conductor diameter: 0,4 ... 0,8 mm;
Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;
Conductor connection direction to PCB: 0; °
Numar poli: 5;
Numar total de conexiuni: 10;
Total number of potentials: 5;
Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Distanta intre pini: 3,5 mm / 0.138 inch;
Latime: 17,5 mm / 0.689 inch;
Inaltime: 13,1 mm / 0.516 inch;
Adancime: 10,5 mm / 0.413 inch;
Tip contact (pluggable connector): Conector mama/priza;
Connector (connection type): for PCB;
Mating direction to the PCB: 90; °
PCB contact: THT;
Culoare: gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Copper alloy;
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,065; MJ
Greutate: 2,5; g
Temperatura lucru: -60 ... +105 °C;
Product Group: 4 (Printed Circuit);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4045454040116;
Customs tariff number: 85369010000;
Pret: 6,51 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-modular-pcb-connector-for-solder-pin-strip-push-button-0-8-mm-oe-pin-spacing-3-5-mm-5-pole-0-50-mm2-gray-151392>