


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 10 MM²;
SUITABLE FOR EX E II APPLICATIONS; SIDE AND CENTER
MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE
CLAMP®; 10,00 MM²; YELLOW**

Ratings per: IEC/EN 60947-7-1;
Tensiune nominala (III/3): 800; V
Tensiune nominala de supratensiune (III/3): 8; kV
Curent nominal: 57; A
Curent nominal 2: 76; A
Legend (ratings): (III / 3) %TM Overvoltage category III / Pollution degree 3;
Tensiune nominala UL (Use Group B): 600; V
Curent nominal UL (Use Group B): 65; A
Tensiune nominala UL (Use Group C): 600; V
Curent nominal UL (Use Group C): 65; A
Certificari: UL 1059;
Tensiune nominala EN (Ex e II): 550; V
Curent nominal (Ex e II): 51; A
Tehnologie conexiune: Push-in CAGE CLAMP®;
Tip actionare: Push-in; Open Tool Slot;
Connectable conductor materials: Copper;
Nominal cross-section: 10 mm²;
Solid conductor: 0,5 ... 16 mm² / 20 ... 6 AWG;
Solid conductor; push-in termination: 4 ... 16 mm² / 14 ... 6 AWG;
Fine-stranded conductor: 0,5 ... 16 mm² / 20 ... 6 AWG;
Fine-stranded conductor; with insulated ferrule: 4 ... 10 mm² / 12 ... 8 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 4 ... 10 mm² / 12 ... 8 AWG;
Strip length: 17 ... 19 mm / 0.67 ... 0.75 inch;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;
Number of jumper slots: 2;
Latime: 10 mm / 0.394 inch;
Inaltime from upper-edge of DIN-rail: 36,9 mm / 1.453 inch;
Adancime: 67,8 mm / 2.669 inch;
Design: horizontal type;
Tip montaj: DIN-35 rail;
Marking level: Center/side marking;
Culoare: yellow;
Material izolator: Polyamide 66 (PA 66);
Greutate: 18,2; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4055143645911;
Customs tariff number: 85369010000;
Pret: 13,36 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-through-terminal-block-10-mm2-suitable-for-ex-e-ii-applications-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-10-00-mm2-yellow-151652>