

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410

	<p><u>WAGO THT MALE HEADER; 1.0 X 1.0 MM SOLDER PIN; STRAIGHT; 100% PROTECTED AGAINST MISMATING; THREADED FLANGE; PIN SPACING 3.5 MM; 2-POLE; LIGHT GRAY</u></p> <p>Ratings per: IEC/EN 60664-1; Tensiune nominala (III/3): 160; V Tensiune nominala de supratensiune (III/3): 2,5; kV Tensiune nominala (III/2): 160; V Tensiune nominala de supratensiune (III/2): 2,5; kV Tensiune nominala (II/2): 320; V Tensiune nominala de supratensiune (II/2): 2,5; kV Curent nominal: 10; A Legend (ratings): (III / 2) % Overvoltage category III / Pollution degree 2; Tensiune nominala UL (Use Group B): 300; V Curent nominal UL (Use Group B): 10; A Tensiune nominala UL (Use Group D): 300; V Curent nominal UL (Use Group D): 10; A Certificari: UL 1059; Tensiune nominala CSA (Use Group B): 300; V Curent nominal CSA (Use Group B): 10; A Tensiune nominala CSA (Use Group D): 300; V Curent nominal CSA (Use Group D): 10; A Numar poli: 2; Total number of potentials: 2; Numar tipuri de conexiuni: 1; Numar nivele: 1; Distanta intre pini: 3.5 mm / 0.138 inch; Latime: 16.5 mm / 0.65 inch; Inaltime: 14.8 mm / 0.583 inch; Inaltime de la fata: 10.3 mm / 0.406 inch; Adancime: 8.5 mm / 0.335 inch; Lungimea pinului de contact: 4,5; mm Solder pin dimensions: 1 x 1 mm; Diametrul de gaurire cu toleranta: 1.4 (+0.1) mm; Tip contact (pluggable connector): Conector tata/fisa; Connector (connection type): for PCBs; Mismatching protection: Yes; Mating direction to the PCB: 90; ° Locking of plug-in connection: Threaded flange; PCB contact: THT; Solder pin arrangement: over the entire male connector, in line; Number of solder pins per potential: 1; Culoare: light gray; Material group: I; Material izolator: Polyamide 66 (PA 66); Flammability class per UL94: V0; Contact material: Cupru electrolitic(ECu); Contact plating: tin-plated; Fire load: 0,02; MJ Greutate: 1,2; g Temperatura lucru: -60 ... +100 °C; Product Group: 3 (Multi Conn. System); Tip ambalare: BOX; Tara de origine: DE; GTIN: 4045454682897; Customs tariff number: 85366990990; Pret: 9,32 lei (TVA inclus)</p> <p>Detalii online: https://www.materialelectrice.ro/tht-male-header-1-0-x-1-0-mm-solder-pin-straight-100-protected-against-mismatching-threaded-flange-pin-spacing-3-5-mm-2-pole-light-gray-151775</p>
--	---