

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410

	<p align="center"><b>WAGO THT MALE HEADER; 1.0 X 1.0 MM SOLDER PIN; ANGLED;              100% PROTECTED AGAINST MISMATING; PIN SPACING 7.5 MM; 10-              POLE; LIGHT GRAY</b></p> <p>Ratings per: IEC/EN 60664-1;              Tensiune nominala (III/3): 500; V              Tensiune nominala de supratensiune (III/3): 6; kV              Tensiune nominala (III/2): 630; V              Tensiune nominala de supratensiune (III/2): 6; kV              Tensiune nominala (II/2): 1000; V              Tensiune nominala de supratensiune (II/2): 6; kV              Curent nominal: 12; A              Legend (ratings): (III / 2) <math>\hat{a}</math>%<sup>TM</sup> Overvoltage category III / Pollution degree 2;              Tensiune nominala UL (Use Group B): 300; V              Curent nominal UL (Use Group B): 15; A              Tensiune nominala UL (Use Group D): 300; V              Curent nominal UL (Use Group D): 10; A              Certificari: UL 1059;              Tensiune nominala UL 1977: 600; V              Curent nominal UL 1977: 10; A              Tensiune nominala CSA (Use Group B): 300; V              Curent nominal CSA (Use Group B): 15; A              Tensiune nominala CSA (Use Group D): 300; V              Curent nominal CSA (Use Group D): 10; A              Numar poli: 10;              Total number of potentials: 10;              Numar tipuri de conexiuni: 1;              Numar nivele: 1;              Distanta intre pini: 7.5 mm / 0.295 inch;              Latime: 75.7 mm / 2.98 inch;              Inaltime: 15.2 mm / 0.598 inch;              Inaltime de la fata: 11.4 mm / 0.449 inch;              Adancime: 12 mm / 0.472 inch;              Lungimea pinului de contact: 3,8; mm              Solder pin dimensions: 1 x 1 mm;              Diametrul de gaurire cu toleranta: 1.4 (+0.1) mm;              Tip contact (pluggable connector): Conector tata/fisa;              Connector (connection type): for PCBs;              Mismatching protection: Yes;              Mating direction to the PCB: 0; °              PCB contact: THT;              Solder pin arrangement: over the entire male connector, in line;              Number of solder pins per potential: 1;              Culoare: light gray;              Material group: I;              Material izolator: Polyamide 66 (PA 66);              Flammability class per UL94: V0;              Contact material: Cupru electrolitic(ECu);              Contact plating: tin-plated;              Fire load: 0,081; MJ              Greutate: 4; g              Temperatura lucru: -60 ... +100 °C;              Product Group: 3 (Multi Conn. System);              Tip ambalare: BOX;              Tara de origine: PL;              GTIN: 4044918870092;              Customs tariff number: 85366990990;              Pret: 15,17 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/tht-male-header-1-0-x-1-0-mm-solder-pin-angled-100-protected-against-mismatching-pin-spacing-7-5-mm-10-pole-light-gray-151986">https://www.materialelectrice.ro/tht-male-header-1-0-x-1-0-mm-solder-pin-angled-100-protected-against-mismatching-pin-spacing-7-5-mm-10-pole-light-gray-151986</a></p>
--	---