

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

	<p><b>WAGO 3-CONDUCTOR, DOUBLE-DECK TERMINAL BLOCK; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM<sup>2</sup>; CAGE CLAMP<sup>®</sup>; 2.50 MM<sup>2</sup>; GRAY</b></p> <p>Ratings per: IEC/EN 60947-7-1; Tensiune nominala (III/3): 500; V Tensiune nominala de supratensiune (III/3): 6; kV Curent nominal: 24; A Legend (ratings): (III / 3) <sup>â%</sup>™ Overvoltage category III / Pollution degree 3; Tehnologie conexiune: CAGE CLAMP<sup>®</sup>; Tip actionare: Operating tool; Connectable conductor materials: Copper; Solid conductor: 0,08 ... 2,5 mm<sup>2</sup> / 28 ... 12 AWG; Fine-stranded conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG; Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch; Numar total de conexiuni: 6; Total number of potentials: 2; Numar nivele: 2; Wiring type: Front-entry wiring; Latime: 5 mm / 0.197 inch; Inaltime from upper-edge of DIN-rail: 40 mm / 1.575 inch; Adancime: 91 mm / 3.583 inch; Design: horizontal type; Tip montaj: DIN-35 rail; Potential marking: PE/N; Marking level: Side marking; Culoare: gray; Material izolator: Polyamide 66 (PA 66); Fire load: 0,204; MJ Greutate: 15,7; g Tip ambalare: BOX; Tara de origine: DE; GTIN: 4045454094508; Customs tariff number: 85369010000; Pret: 23,80 lei (TVA inclus)</p> <p>Detalii online: <a href="https://www.materialelectrice.ro/3-conductor-double-deck-terminal-block-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-cage-clamp-2-50-mm2-gray-152100">https://www.materialelectrice.ro/3-conductor-double-deck-terminal-block-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-cage-clamp-2-50-mm2-gray-152100</a></p>
--	--