


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**WAGO 2-CONDUCTOR END TERMINAL BLOCK; SUITABLE FOR EX I APPLICATIONS; WITHOUT PUSH-BUTTONS; WITH FIXING FLANGE M4; FOR SCREW OR SIMILAR MOUNTING TYPES; FIXING HOLE 4.2 MM  $\tilde{\sim}$ ; 2.5 MM $\hat{A}$ <sup>2</sup>; CAGE CLAMP $\hat{A}$ ; 2,50 MM $\hat{A}$ <sup>2</sup>; BLUE**

Tensiune nominala (III/3): 500; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Curent nominal: 24; A  
Legend (ratings): (III / 3)  $\hat{A}$ %<sup>TM</sup> Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: CAGE CLAMP $\hat{A}$ ;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 0.08 ... 2.5 mm $\hat{A}$ <sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0.08 ... 4 mm $\hat{A}$ <sup>2</sup> / 28 ... 12 AWG;  
Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;  
Numar total de conexiuni: 2;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Latime: 5 mm / 0.197 inch;  
Inaltime de la fata: 27.6 mm / 1.087 inch;  
Adancime: 33.4 mm / 1.315 inch;  
Design: horizontal;  
Tip montaj: Mounting flange;  
Marking level: Side marking;  
Culoare: blue;  
Fire load: 0,076; MJ  
Greutate: 4,2; g  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4044918480444;  
Customs tariff number: 85369010000;  
Pret: 5,37 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-end-terminal-block-suitable-for-ex-i-applications-without-push-buttons-with-fixing-flange-m4-for-screw-or-similar-mounting-types-fixing-hole-4-2-mm-oe-2-5-mm2-cage-clamp-2-50-mm2-blue-152233>