

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

**ERSE CABLU RE-Y(ST)YSWAY-FL (MULTIPAIR) 16 X 2 X 1.3 , ERSE**

Construc?ie

1. CONDUCTOR IEC-60228, VDE 0295, EN 60228
2. IZOLARE EN 50290-2-21 PVC combinate
3. Cod culoare BS-5308 PARTEA A-2 sau alb-negru;  
Fiecare pereche numerotate
4. E?uare perechi, perechi, în straturi ?i
- 1 NUM?R COMUNICARE CORE
5. Placarea cu band? de PES
6. GENERAL SCREEN cupru cositorit DRAIN fir; TAPE AL-PES
7. INNER MANTAUA EN 50290-2-22 PVC combinate
8. Armour GALVANIZAT sârme de o?el ROTUNDE
9. MANTAUA EN 50290-2-22 PVC combinate
10. MANTAUA CULOARE RAL 5015 \* BLUE; RAL 9005 \* BLACK  
cei care nu

Caracteristici tehnice

1. Rezisten?a conductorului (MAX) 0.50 mm<sup>2</sup> = 36 Ω / km  
0,75 mm<sup>2</sup> = 24.5 Ω / km  
1,0 mm<sup>2</sup> = 18.1 Ω / km  
1.30 mm<sup>2</sup> = 13.9 Ω / km  
1,5 mm<sup>2</sup> = 12.1 Ω / km
2. Rezisten?a de izola?ie (min) 100 MΩXKm
3. CAPACITATE MUTUAL (MAX) 0.50 mm<sup>2</sup> = 120 pF / m  
0,75 mm<sup>2</sup> = 120 pF / m  
1,0 mm<sup>2</sup> = 120 pF / m  
1,3 mm<sup>2</sup> = 130 pF / m  
1,5 mm<sup>2</sup> = 130 pF / m
4. Gam? de temperatur? - 30 ° C ~ +70 ° C (de stabilire a fixe)
5. FLACARA TEST IEC 60332-3-24; VDE 0482-266-2-4  
RO 50266-2-4/BS EN 50266-2-4
6. L / R (raport) (MAX) 0.50 mm<sup>2</sup> = 25 mH / Ω  
0,75 mm<sup>2</sup> = 25 mH / Ω  
1,0 mm<sup>2</sup> = 25 mH / Ω  
1.30 mm<sup>2</sup> = 40 mH / Ω  
1.50 mm<sup>2</sup> = 40 mH / Ω
7. Curentul de sarcin? (25 ° C) 0.50 mm<sup>2</sup> = 6,0 A  
0,75 mm<sup>2</sup> = 13 A  
1,0 mm<sup>2</sup> = 16 A  
1,30 mm<sup>2</sup> = 18 A  
1,5 mm<sup>2</sup> = 20 A
8. Tensiunea de lucru 300/500 V.
9. TEST VOLTAJGE Core / Core = 2,000 V.  
Core / Ecran = 2,000 V.
10. Indoire 10X cablu Ø  
cerere

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/cablu-re-y-st-ysway-fl-multipair-16-x-2-x-1-3-erse>

