

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

ERSE CABLU RE-2X(ST)YSWAY-FL (MULTICORE) 19 X 1.5, ERSE

Construc?ie

1. CONDUCTOR IEC-60228, VDE 0295, EN 60228
2. IZOLARE EN 50290-2-29 XLPE
3. COD CORES Culoare Alb izolate cu negru
- NUM?RUL IMPRINTED
4. E?uare în straturi de bitum OPTIMUM
5. Placarea cu band? de PES
6. GENERAL SCREEN cupru cositorit DRAIN fir; TAPE AL-PES
7. INNER MANTAU EN 50290-2-22 PVC combinate
8. Armour GALVANIZAT sârme de o?el ROTUNDE
9. MANTAU EN 50290-2-22 PVC combinate
10. MANTAU CULOARE RAL 5015 * BLUE; RAL 9005 * BLACK

cei care nu

- CEM bune * CARACTERISTICI
 - Raza de îndoire MICI
 - FLAME RETARDANT ?i rezistent AYDROCARBON
 - Fl * = FLAME RETARDANT manta exterioara
 - Yv * = manta exterioara ARMAT
 - RAL 5015 MANTA BLUE *: conexiunilor EX-Proof
- IN explozive ?i IN FLAMMABLE
MEDIU.
- RAL 9005 BLACK MANTA *: Locuri in care rezistenta UV
ESTE NECESAR?
 - RAL 7032 GREY MANTA *: INTERIORUL CL?DIRILOR

Caracteristici tehnice

1. Rezisten?a conductorului 0,50 mm² = 36 OHM / km
0,75 mm² = 24.5 OHM / km
1,0 mm² = 18.1 OHM / km
1,5 mm² = 12.1 OHM / km
2,5 mm² = 7,4 OHM / km
2. Rezisten?a de izola?ie (MIN) 5000 m OHMxkm
3. CAPACITATE MUTUAL (MAX) 0.50 mm² = 115 pF / m
0,75 mm² = 115 pF / m
1,0 mm² = 115 pF / m
1,5 mm² = 115 pF / m
2,5 mm² = 115 pF / m
4. Gam? de temperatur? - 30 ° C ~ +90 ° C (de stabilire a fixe)
5. FLAME PROPAGARII IEC 60332-3-24; VDE 0482-266-2-4
RO 50266-2-4/BS EN 50266-2-4
6. L / R (raport) (MAX) 0.50 mm² = 25 mH / OHM
0,75 mm² = 25 mH / OHM
1,0 mm² = 25 mH / OHM
1,5 mm² = 40 mH / OHM
2,5 mm² = 60 mH / OHM
7. Curentul de sarcin? (25 ° C) 0.50 mm² = 6,0 A
0,75 mm² = 13 A
1,0 mm² = 16 A
1,5 mm² = 20 A
2,5 mm² = 25 A
8. Tensiunea de lucru 300/500 V.
9. TEST VOLTAJGE Core / Core = 2,000 V.
Core / Ecran = 2,000 V.
10. Indoire 10X cablu Ø

cerere

1. INSTRUMENTATION ?I Control Engineering analogice ?i de transmitere a semnalului digital

INDUSTRIA CHIMIE 2.IN

INDUSTRIA 3.PETROCHEMISTRY

PLANTE 4.POWER

5.INDOORS ?i în aer liber, medii uscate, umede ?i umede

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/cablu-re-2x-st-ysway-fl-multicore-19-x-1-5-erse>

