


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

**ERSE CABLU RE-2X(ST)H-FL (MULTIPAIR) 1 X 2 X 1.5, ERSE**



Construc?ie

1. CONDUCTOR IEC-60228, VDE 0295, EN 60228
2. IZOLARE EN 50290-2-29 XLPE
3. Codul culorilor BS-5308 PARTEA-1 sau negru-alb  
Fiecare pereche numerotate
4. E?uare perechi, perechi, în straturi ?i
5. Placarea cu band? de PES
6. SCREEN cupru cositorit DRAIN fir; TAPE AL-PES
7. MANTAUA EN 50290-2-27 LZSH COMBinate
8. MANTAUA CULOARE RAL 5015 \* BLUE; RAL 9005 BLACK 02 \*  
RAL 7001 GREY

cei care nu

- CEM bune \* CARACTERISTICI
- RETARDANT flac?r? ?i
- REZISTENT LA HIDROCARBURI
- Raza de îndoire MICI
- Fumigen
- F?R? otravit si
- gaze COROZIVE
- RAL 5015 MANTA BLUE \*: IN exploziv ?i izbucneasc?

Locuri ca EX-DOVADA

CONECTAREA

- RAL 9005 BLACK MANTA \*: Locuri in care rezistenta UV

ESTE NECESAR?

- RAL 7001 GREY MANTA \*: INTERIORUL CL?DIRILOR

Caracteristici tehnice

1. CONDUCTOR resistan (min) 0.50 mm<sup>2</sup> = 36 OHM / km  
0,75 mm<sup>2</sup> = 24.5 OHM / km  
1,0 mm<sup>2</sup> = 18.1 OHM / km  
1.30 mm<sup>2</sup> = 13.9 OHM / km  
1,5 mm<sup>2</sup> = 12.1 OHM / km
2. Rezi?en?a de izola?ie (MIN) 5000 m OHM XKm
3. CAPACITATE MUTUAL (MAX) 0.50 mm<sup>2</sup> = 65 pF / m  
0,75 mm<sup>2</sup> = 65 pF / m  
1,0 mm<sup>2</sup> = 65 pF / m  
1.30 mm<sup>2</sup> = 75 pF / m  
1,5 mm<sup>2</sup> = 75 pF / m
4. Gam? de temperatur? - 3 ° C ~ +9 ° C (de stabilire a fixe)
5. L / R (raport) (MAX) 0.50 mm<sup>2</sup> = 25 mH / OHM  
0,75 mm<sup>2</sup> = 25 mH / OHM  
1,0 mm<sup>2</sup> = 25 mH / OHM  
1.30 mm<sup>2</sup> = 40 mH / OHM  
1,5 mm<sup>2</sup> = 40 mH / OHM
6. Curentul de sarcin? (25 ° C 0.50 mm<sup>2</sup> = 6,0 A  
0,75 mm<sup>2</sup> = 13 A  
1,0 mm<sup>2</sup> = 16 A  
1,30 mm<sup>2</sup> = 18 A  
1,5 mm<sup>2</sup> = 20 A
7. Tensiunea de lucru 300/500 V.
8. TEST VOLTAJGE Core / Core = 2,000 V.  
Core / Ecran = 2,000 V.
9. Raza de îndoire 7.5X cablu Ø
10. FLACARA TEST IEC 60332-3-24; VDE 0482-266-2-4  
RO 50266-2-4/BS EN 50266-2-4
11. FUM DENSITATE IEC 61034-2/VDE 0482-1034-2  
RO 61034-2/BS EN 61034-2
12. Test pe corozivitatea gaze de ardere IEC 60754-2/VDE 0482-267-2-3  
RO 50267-2-3/BS EN 50267-2-3
13. TEST f?r? halogen IEC 60754-1, VDE 0482-267-2-1  
RO 50267-2-1/BS EN 50267-2-1

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/cablu-re-2x-st-h-fl-multipair-1-x-2-x-1-5-erse>