

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

ERSE CABLU RE-2X(ST)H-PIMF 24 X 2 X 1.5, ERSE



Construc?ie

1. CONDUCTOR IEC-60228, VDE 0295, EN 60228
 2. IZOLARE EN 50290-2-29 XLPE
 3. Codul culorilor BS-5308 PARTEA-1 sau negru-alb
- Fiecare pereche numerotate
6. Placarea cu band? de PES
 7. GENERAL SCREEN cupru cositorit DRAIN fir; TAPE AL-PES
 8. MANTAUA EN 50290-2-27 LZSH COMBIMATE
 9. MANTAUA CULOARE RAL 5015 * BLUE; RAL 7001 GERY *
RAL 9005 BLACK

CARACTERISTICI

- RETARDANT flac?r? ?i
- REZISTENT LA HIDROCARBURI

- Raza de îndoire MICI

- Fumigen

- F?R? otravit si

Gaze COROZIVE

- RAL 5015 MANTA BLUE *: IN exploziv ?i izbucneasc?

Locuri ca EX-DOVADA

CONECTAREA

- RAL 9005 BLACK MANTA *: Locuri in care rezistenta UV

ESTE NECESAR?

- RAL 7001 GREY MANTA *: INTERIORUL CL?DIRILOR

Caracteristici tehnice

1. Rezisten?a conductorului 0,50 mm² = 36 OHM / km

0,75 mm² = 24.5 OHM / km

1,0 mm² = 18.1 OHM / km

1.30 mm² = 13.9 OHM / km

1,5 mm² = 12.1 OHM / km

2. Rezisten?a de izola?ie (MIN) 5000 m OHMxkm

3. CAPACITATE MUTUAL (MAX) 0,50 mm² = 100 pF / m

0,75 mm² = 100 pF / m

1,0 mm² = 100 pF / m

1,30 mm² = 100 pF / m

1,5 mm² = 100 pF / m

4. Gam? de temperatur? - 30 ° C ~ +90 ° C (de stabilire a fixe)

5. L / R (raport) (MAX) 0.50 mm² = 25 mH / OHM

0,75 mm² = 25 mH / OHM

1,0 mm² = 25 mH / OHM

1.30 mm² = 40 mH / OHM

1,5 mm² = 40 mH / OHM

6. Curentul de sarcin? (25 ° C) 0.50 mm² = 6,0 A

0,75 mm² = 13 A

1,0 mm² = 16 A

1,30 mm² = 18 A

1,5 mm² = 20 A

7. Tensiunea de lucru 300/500 V.

8. TEST VOLTAJGE Core / Core = 2,000 V.

Core / Ecran = 2,000 V.

9. Raza de îndoire 7.5X cablu Ø

10. FLACARA TEST IEC 60332-3-24; VDE 0482-266-2-4

RO 50266-2-4/BS EN 50266-2-4

11. FUM DENSITATE IEC 61034-2/VDE 0482-1034-2

RO 61034-2/BS EN 61034-2

12. Test pe corozivitatea gaze de ardere IEC 60754-2/VDE 0482-267-2-3

RO 50267-2-3/BS EN 50267-2-3

13. TEST f?r? halogen CE 60754-1, VDE 0482-267-2-1

RO 50267-2-1/BS EN 50267-2-1

Cerere

Medii de interior INTENS populat de oameni atunci cand exista interferen?e electromagnetice.

1. INSTRUMENTATION SI CONTROL ENGINEERING ANALOG

?I transmitere a semnalului digital

Rafin?riile 2. PETROLEUM

INDUSTRIA 3. PETROCHEMISTRY

PLANTE 4. POWER

5. NATURAL sta?ii de pompare GAZ

LOCURI 6. DRY-umede ?i umede, LA INTERIOR

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/cablu-re-2x-st-h-pimf-24-x-2-x-1-5-erse>