

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

ERSE CABLU CAT-5E UTP, 4 X2 X24 AWG, ERSE



construc?ie

1. CONDUCTOR ELEKTROLYTIC conductor de cupru 0,51 Ø (24 AWG)
2. Izola?ia solid? izola?ie din polietilen? 1,00 Ø
3. SCREEN TWIST COMUN AL 4 perechi
4. MANTAUA FR-PC COMPONENTE 5,60 Ø
5. MANTAUA CULOARE RAL 7032 GREY

Caracteristici tehnice

1. Rezisten?a conductorului 94 Ω / km
2. Rezisten?a izola?iei 5000 MΩ.km
3. REZISTEN?A DEZECHILIBRATE% 3
4. Tensiune de 250 V
5. TEST VOLTAJI CORE / CORE 1200 V
6. Beding RADIUS 8 X Cablo Ø
7. CARACTERISTICI impedan?? 100 15 Ω
8. Temperatur? -20 ° C + 60 ° C
9. FLACARA TEST IEC 60332-1-2, VDE 0482-332-1-2 EN 60332-1-2
10. Capacitate mutuala (1 KHz) 52 pF / m
11. Viteza de propagare% 67

cerere

- 1.10 BaseT (IEEE 802.3) ETHERNET
- 2.100 BaseT (IEEE 802.3u) Fast Ethernet
- 3.100 VG-AnyLAN (IEEE 802.12)
- 4.4/16 Mbps Token Ring (IEEE 802.5)
- 5.100 Mbps CDDI
- 6.52/155 Mbps ATM
- 7.1000 Base T (Gigabit Ethernet) (IEEE 802.3 AB)
- 8.NOTE: Este potrivit pentru transmiterea de semnale analogice ?i digitale de pân? la 155 Mbit / sec.

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/cablu-cat-5e-utp-4-x2-x24-awg-erse>