

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



GEWISS P-COMFORT - LOAD MANAGEMENT RELAY - ZIGBEE

Descriere - Load management relay p-comfort (radio frequency version)
Model - Radio frequency version
Tensiune nominală (V) - 230 c.a.
Nr. module EN 50022 - 2
Curent nominal - 32 A
Tip Contact cu releu - Changeover (potential free contact)
capacitate Contact cu releu - 16 A AC1 250 V
Standard - EN 60669-1, EN 60669-2-1, EN 301489-1, EN 301489-17
Frecvență nominală (Hz) - 50
Tensiune de izolare - 1000 V
Tensiune nominală de rezistență la impulsuri - 1 kV
Cablul cu secțiune rigidă - Max 6 mm²
Cablul cu secțiune flexibilă - Max 4 mm²
Rigid cable section for contact terminals - Max 4 mm²
Flexible cable section for contact terminals - Max 2,5 mm²
Temperatură de operare - -5 +45 °C
Temperatură de stocare - -25 +70 °C
Absorbed power with In - 2 VA
Sound level at 10 cm - 85 Db
Max outdoor distance of signal - 100 m
Max number of Zigbee devices can be connected - 10
Radio protocol - ZigBee / IEEE 802.15.4
Output power of signal - +8 dBm
Frequency of signal - 2.4
Dimensiuni măsurate - Active power (absorbed and supplied), active energy (absorbed and supplied), current, voltage, power factor, frequency
Resetting of energy count - Da
Acoustic warning threshold exceeded - Da
Adjustment power range - 0 ÷ 8 kW (3,8 kW default)
Adjustment of non-priority load contact opening delay time - 10 ÷ 120 s (45 s default)
Adjustment of non-priority load contact opening time - 10 ÷ 255 s (90 s default)
Electrocod - 051A
Ware number - 85389099
Pret: 716,03 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/p-comfort-load-management-relay-zigbee-213837>