

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**GEWISS PROIECTOR LED TIP SMART [PRO] 2.0 - 2 MODULE -
DIMABIL DALI - CIRCULAR C1 - 3000K (CRI 70) - IP66 - PROTECTION
CLASS II**

GENERAL INFORMATION - -

OPTIC AND ILLUMINATING FEATURES - -

Context - Sport, Big Areas

OpticĂf - C1 - Circular 30°

Luminaire - LED luminaire with small, mid and high lumen power

Unified Glare Rating - G*6 - ULOR = 0

AplicaĂie - Intern / Extern

LuminĂf ieĂf ire (lm) - 37300

Unique digital code (Datamatrix) - Currently not present

Efficiency

(lm/W) - 113

Culoare - Gri grafit

Culoare TemperaturĂf - 3000 K

Tip sursĂf de luminĂf - LED - Neinlocuibil

Color Rendering Index - CRI>70

Puterea sistemului - 330 W

Standard Deviation Colour Matching - SDCM = 5

LED Lifetime - L90B10(Tq25°C)=40.000h; L80B10(Tq25°C)=90.000h

Photobiological Risk Class - -

Greutate (Kg) - 13

Standard - EN60598-1; EN60598-2-5; IEC 62778; IEC 62471; EN13201

GaranĂie - 5 ani

ELETRICAL AND LIGHTING FEATURES - -

TemperaturĂf de stocare - -

Tensiune de alimentare - 220 - 240 V

Operating temperature - -30 +50 °C

FrecvenĂf nominalĂf (Hz) - 50 / 60

MATERIALS - -

Driver - Included

Body - Aluminiu turnat

Driver failure rate - F10 = 100.000h Tq25°C

Ecran - Flat tempered glass 4mm

Overvoltage protection - DM 6 kV / CM 10 kV

Optic - Polished quartz and metallized PC HT reflector

Control System - DALI

Gasket - Anti-aging silicone

INSTALLATION AND MAINTENANCE - -

Locking Hook - Hexagonal metric screws

Mouting and installation - High-mast lighting - Wall mounting - Ground mouting

External screw - Stainless steel

Tilt - Rotation on bracket with integrated goniometer

Colour - Polyester powder coated

Wiring - Watertight connector

STANDARDS AND APPROVALS - -

Prindere - ConsolĂf

Clasificare - -

Optic Maintenance - Not available

Dispozitiv cu temperaturĂf la suprafaĂf redusĂf - Nu

LED Maintenance - Not available

Certificare DIN 18032-3 - Da

Driver Box - Integrat

IPEA - -

SuprafaĂf maximĂf expusĂf la vant - 0,170 m2

ClasĂf izolaĂie - II

- - -

ClasĂf de protecĂie IP - IP66

- - -

Cod IK - IK08

- - -

Glow Test conductori - -

- - -

Ware number - 94054010

Pret: 4 561,81 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/proieCTOR-led-tip-smart-pro-2-0-2-module-dimabil-dali-circular-c1-3000k-cri-70-ip66-protection-class-ii-215452>