


Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**GEWISS PROJECTOR LED TIP SMART [PRO] 2.0 - 2+2 MODULE -  
SYMMETRICAL S1 - 3000K (CRI 70) - IP66 - PROTECTION CLASS I**

GENERAL INFORMATION - -  
OPTIC AND ILLUMINATING FEATURES - -  
Context - Sport, Big Areas  
Optic - S1 - Symmetric Wide  
Luminaire - LED luminaire with mid and high lumen power  
Unified Glare Rating - G\*6 - ULOR = 0  
Application - Intern / Extern  
Luminous Flux (lm) - 73200  
Unique digital code (Datamatrix) - Currently not present  
Efficiency  
(lm/W) - 111  
Culoure - Gri grafit  
Culoare Temperatur - 3000 K  
Tip sursă de lumină - LED - Neînlocuibil  
Color Rendering Index - CRI>70  
Puterea sistemului - 660 W  
Standard Deviation Colour Matching - SDCM = 3  
LED Lifetime - L90B10(Tq25°C)=40.000h; L80B10(Tq25°C)=90.000h  
Photobiological Risk Class - -  
Greutate (Kg) - 15  
Standard - EN60598-1; EN60598-2-5; IEC 62778; IEC 62471; EN13201  
Garanție - 5 ani  
ELECTRICAL AND LIGHTING FEATURES - -  
Temperatură de stocare - -  
Tensiune de alimentare - -  
Operating temperature - -30 +50 °C  
Frecvență nominală (Hz) - -  
MATERIALS - -  
Driver - To be ordered separately  
Body - Aluminiu turnat  
Driver failure rate - See external supply unit  
Ecran - Flat tempered glass 4mm  
Overvoltage protection - See external supply unit  
Optic - Polished quartz and metallized PC HT reflector  
Control System - See external supply unit  
Gasket - Anti-aging silicone  
INSTALLATION AND MAINTENANCE - -  
Locking Hook - Hexagonal metric screws  
Mounting and installation - High-mast lighting - Wall mounting - Ground mounting  
External screw - Stainless steel  
Tilt - Rotation on bracket with integrated goniometer  
Colour - Polyester powder coated  
Wiring - Watertight connector  
STANDARDS AND APPROVALS - -  
Prindere - Consolă  
Clasificare - -  
Optic Maintenance - Not available  
Dispozitiv cu temperatură la suprafață redusă - Nu  
LED Maintenance - Da  
Certificare DIN 18032-3 - -  
Driver Box - Exterior  
IPEA - -  
Suprafață maximă expusă la vant - 0,222 m2  
Clasă izolație - I  
- - -  
Clasă de protecție IP - IP66  
- - -  
Cod IK - IK08  
- - -  
Glow Test conductori - -  
- - -  
Ware number - 94054010  
Pret: 8 329,32 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/proiector-led-tip-smart-pro-2-0-2-2-module-symmetrical-s1-3000k-cri-70-ip66-protection-class-i-215566>