

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**GEWISS PROJECTOR LED TIP SMART [PRO] 2.0 - 2+2 MODULE -
CIRCULAR C1 - 3000K (CRI 70) - IP66 - PROTECTION CLASS I**

GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Sport, Big Areas
Optic - C1 - Circular 30°
Luminaire - LED luminaire with mid and high lumen power
Unified Glare Rating - G*6 - ULOR = 0
Application - Intern / Extern
Luminous Flux (lm) - 74600
Unique digital code (Datamatrix) - Currently not present
Efficiency
(lm/W) - 113
Cooling - Graphite
Cooling Temperature - 3000 K
Light Source - LED - Non-replaceable
Color Rendering Index - CRI > 70
Power - 660 W
Standard Deviation Colour Matching - SDCM = 3
LED Lifetime - L90B10(Tq25°C)=40.000h; L80B10(Tq25°C)=90.000h
Photobiological Risk Class - -
Weight (Kg) - 15
Standard - EN60598-1; EN60598-2-5; IEC 62778; IEC 62471; EN13201
Warranty - 5 years
ELECTRICAL AND LIGHTING FEATURES - -
Storage Temperature - -
Supply Voltage - -
Operating temperature - -30 +50 °C
Nominal Frequency (Hz) - -
MATERIALS - -
Driver - To be ordered separately
Body - Aluminium
Driver failure rate - See external supply unit
Screen - Flat tempered glass 4mm
Overvoltage protection - See external supply unit
Optic - Polished quartz and metallized PC HT reflector
Control System - See external supply unit
Gasket - Anti-aging silicone
INSTALLATION AND MAINTENANCE - -
Locking Hook - Hexagonal metric screws
Mounting and installation - High-mast lighting - Wall mounting - Ground mounting
External screw - Stainless steel
Tilt - Rotation on bracket with integrated goniometer
Colour - Polyester powder coated
Wiring - Watertight connector
STANDARDS AND APPROVALS - -
Certification - Consol
Classification - -
Optic Maintenance - Not available
Temperature protection at the surface - No
LED Maintenance - Yes
Certification DIN 18032-3 - -
Driver Box - Exterior
IPEA - -
Maximum surface area exposed to wind - 0,222 m2
Class of insulation - I
- - -
Protection Class IP - IP66
- - -
IK Code - IK08
- - -
Glow Test conductors - -
- - -
Warehouse number - 94054010
Price: 8 341,56 lei (TVA incl.)

Details online: <https://www.materialelectrice.ro/proiector-led-tip-smart-pro-2-0-2-2-module-circular-c1-3000k-cri-70-ip66-protection-class-i-215573>