

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**GEWISS LAMPA STRADALA ROAD [5] - MEDIUM - 5 (5X3 LED) -  
BIPOWER WITH SELF-LEARNING - HUGE OPTIC - 3000 K - 0.85A -  
IP66 - CLASS II**

GENERAL INFORMATION - -  
OPTIC AND ILLUMINATING FEATURES - -  
Context - Street and parking lighting  
Optic - HUGE  
Luminaire - LED Road Equipment  
Unified Glare Rating - G\*3 - ULOR = 0  
Aplicatie - Exterior  
Luminanta (lm) - 15300  
Unique digital code (Datamatrix) - Currently not present  
Efficiency  
(lm/W) - 95  
Culoare - Gri grafit  
Culoare Temperaturaf - 3000 K  
Tip sursaf de luminantaf - LED - Neinlocuibil  
Color Rendering Index - CRI>70  
System  
power - 161 W @ 0.85A  
Standard Deviation Colour Matching - SDCM = 5  
LED Lifetime - L90B10(Tq25°C)>115.000h; L90B10(Tq40°C)=115.000h  
Photobiological Risk Class - RG0  
Greutate (Kg) - 8.8  
Standard - EN 60598-2-3, EN 60598-1 IEC/TR 62778  
Garanafie - 5 ani  
ELECTRICAL AND LIGHTING FEATURES - -  
Temperaturaf de stocare - -  
Tensiune de alimentare - 220 - 240 V  
Operating temperature - -25 +40 °C  
Frecvenaf nominalaf (Hz) - 50 / 60  
MATERIALS - -  
Driver failure rate - F10 = 100.000h Tq25°C/50.000h Tq40°C  
Body - Aluminiu turnat  
Driver - Included  
Ecran - 4mm thick flat tempered glass  
Overvoltage protection - DM 10KV / CM 10KV  
Optic - Metallized polycarbonate reflector  
Control System - Regim dual cu autoinvafafare  
Gasket - Anti-aging silicone  
INSTALLATION AND MAINTENANCE - -  
Locking Hook - Integrated front handle  
Mounting and installation - Pole Head - Outreach  
External screw - Oafel  
Tilt - Console cu acces pe lateralaf-20° ÷ +10° - -10° ÷ +20° cap de stalp  
Colour - Powder coating  
Wiring - Intrerupafitor secafionator  
STANDARDS AND APPROVALS - -  
Prindere - Pole Head - Outreach  
Clasificare - -  
Optic Maintenance - Not available  
Dispozitiv cu temperaturaf la suprafafaf redusaf - -  
LED Maintenance - Not available  
Certificare DIN 18032-3 - -  
Driver Box - Integrat  
IPEA - -  
Suprafafaf maximaf expusaf la vant - 0.19 m<sup>2</sup>  
Clasaf izolafie - II  
- - -  
Clasaf de protecfie IP - IP66  
- - -  
Cod IK - IK08  
- - -  
Glow Test conductori - -  
- - -  
Ware number - 94054039  
Pret: 3 999,32 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/lampa-stradala-road-5-medium-5-5x3-led-bipower-with-self-learning-huge-optic-3000-k-0-85a-ip66-class-ii-215755>