

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**GEWISS LAMPA STRADALA ROAD [5] - MINI - 2 (2X3 LED) - DALI -  
WIDE OPTIC - 3000 K - 1A - IP66 - CLASS II**

GENERAL INFORMATION - -  
OPTIC AND ILLUMINATING FEATURES - -  
Context - Street and parking lighting  
Optic - WIDE  
Luminaire - LED Road Equipment  
Unified Glare Rating - G\*3 - ULOR = 0  
Aplicatie - Exterior  
Luminaria (lm) - 7400  
Unique digital code (Datamatrix) - Currently not present  
Efficiency  
(lm/W) - 96  
Culoare - Gri grafit  
Culoare Temperatur - 3000 K  
Tip sursa de lumina - LED - Neinlocuibil  
Color Rendering Index - CRI>70  
System  
power - 77 W @ 1A  
Standard Deviation Colour Matching - SDCM = 5  
LED Lifetime - L90B10(Tq25°C)>115.000h; L90B10(Tq40°C)=115.000h  
Photobiological Risk Class - RG0  
Greutate (Kg) - 6.6  
Standard - EN 60598-2-3, EN 60598-1 IEC/TR 62778  
Garantie - 5 ani  
ELECTRICAL AND LIGHTING FEATURES - -  
Temperatur de stocare - -  
Tensiune de alimentare - 220 - 240 V  
Operating temperature - -25 +40 °C  
Frecventa nominala (Hz) - 50 / 60  
MATERIALS - -  
Driver failure rate - F10=100.000h Tq25°C/75.000h Tq40°C  
Body - Aluminiu turnat  
Driver - Included  
Ecran - 4mm thick flat tempered glass  
Overvoltage protection - DM 10KV / CM 10KV  
Optic - Metallized polycarbonate reflector  
Control System - DALI  
Gasket - Anti-aging silicone  
INSTALLATION AND MAINTENANCE - -  
Locking Hook - Integrated front handle  
Mounting and installation - Pole Head - Outreach  
External screw - Oel  
Tilt - Console cu acces pe laterala -20° ÷ +10° - -10° ÷ +20° cap de stalp  
Colour - Powder coating  
Wiring - Intreruptor securizator  
STANDARDS AND APPROVALS - -  
Prindere - Pole Head - Outreach  
Clasificare - -  
Optic Maintenance - Not available  
Dispozitiv cu temperatura la suprafata redus - -  
LED Maintenance - Not available  
Certificare DIN 18032-3 - -  
Driver Box - Integrat  
IPEA - -  
Suprafata maxima expusa la vant - 0,15 m<sup>2</sup>  
Clasificatie izolatie - II  
- - -  
Clasificatie de protectie IP - IP66  
- - -  
Cod IK - IK08  
- - -  
Glow Test conductori - -  
- - -  
Ware number - 94054039  
Pret: 2 439,85 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/lampa-stradala-road-5-mini-2-2x3-led-dali-wide-optic-3000-k-1a-ip66-class-ii-215836>