

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**GEWISS CORP DE ILUMINAT CU LED LINIAR ETANS SMART[3] PLUS**  
**- 1200 - TRANSPARENT DIFFUSER - ON / OFF - STAND ALONE -**  
**3.000K CRI>80**

GENERAL INFORMATION - -  
OPTIC AND ILLUMINATING FEATURES - -  
Context - Lighting of warehouses, indoor parking and industrial production rooms  
Optic - Microprismatic transparent  
Luminaire - LED fixture for general lighting  
Unified Glare Rating - UGR  $\leq$  25 (4H/4H)  
Aplicatie - Intern  
Luminanta (lm) - 5400  
Unique digital code (Datamatrix) - Datamatrix  
Efficiency  
(lm/W) - 150  
Culoare - Gri RAL 7035  
Culoare Temperatur - 3000 K  
Tip sursa de lumina - LED - Neinlocuibil  
Color Rendering Index - CRI>80  
Puterea sistemului - 36 W  
Standard Deviation Colour Matching - SDCM = 3  
LED Lifetime - L90B10(Tq25°C)=50.000h; L80B10(Tq25°C)=100.000h  
Photobiological Risk Class - RG0  
Greutate (Kg) - 2.4  
Standard - EN60598-1; IEC 62778; IEC62471  
Garantie - 5 ani  
ELECTRICAL AND LIGHTING FEATURES - -  
Temperatur de stocare - -25 +80 °C  
Tensiune de alimentare - 220-240 V  
Operating temperature - -25 +50 °C  
Frecventa nominala (Hz) - 50/60 Hz  
MATERIALS - -  
Driver - Included  
Body - Polycarbonate  
Driver failure rate - F10 = 100.000h Tq25°C  
Ecran - UV stabilised polycarbonate  
Overvoltage protection - DM 1KV / CM 2KV  
Optic - Integrated in the screen  
Control System - Stand Alone - On / Off  
Gasket - CNC deposited sealant  
INSTALLATION AND MAINTENANCE - -  
Locking Hook - -  
Mounting and installation - Ceiling - Wallmounting - Suspension  
External screw - -  
Tilt - With fixing bracket  
Colour - RAL7035 colored PC paste  
Wiring - With GW connect watertight connector  
STANDARDS AND APPROVALS - -  
Prindere - Stainless steel support  
Clasificare - -  
Optic Maintenance - Not available  
Dispozitiv cu temperatura la suprafata redus - Da  
LED Maintenance - Not available  
Certificare DIN 18032-3 - Not available  
Driver Box - Integrat  
IPEA - -  
Suprafata maxima expusa la vant - -  
Clasificatie izolare - II  
- - -  
Clasificatie de protectie IP - IP66/IP69  
- - -  
Cod IK - IK08  
- - -  
Glow Test conductori - 850 °C  
- - -  
Ware number - 94051040  
Pret: 724,58 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/corp-de-iluminat-cu-led-liniar-etans-smart-3-plus-1200-transparent-diffuser-on-off-stand-alone-3-000k-cri-80-216313>