

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**GEWISS CORP DE ILUMINAT CU LED LINIAR ETANS SMART[3] PLUS  
- 1200 - DIFUZOR OPAL - DALI - CONECTOR CONEXIUNE RAPIDA -  
5.700K CRI>80**

GENERAL INFORMATION - -  
OPTIC AND ILLUMINATING FEATURES - -  
Context - Lighting of warehouses, indoor parking and industrial production rooms  
Optic - Wide opal  
Luminaire - LED fixture for general lighting  
Unified Glare Rating - UGR  $\leq$  25 (4H/8H)  
Aplicatie - Intern  
Luminanta (lm) - 5400  
Unique digital code (Datamatrix) - Datamatrix  
Efficiency  
(lm/W) - 142  
Culoare - Gri RAL 7035  
Culoare Temperaturaf - 5700 K  
Tip sursaf de luminaf - LED - Neinlocuibil  
Color Rendering Index - CRI>80  
Puterea sistemului - 38 W  
Standard Deviation Colour Matching - SDCM = 3  
LED Lifetime - L90B10(Tq25°C)=50.000h; L80B10(Tq25°C)=100.000h  
Photobiological Risk Class - RG0  
Greutate (Kg) - 2.4  
Standard - EN60598-1; IEC 62778; IEC62471  
Garanafie - 5 ani  
ELECTRICAL AND LIGHTING FEATURES - -  
Temperaturaf de stocare - -25 +80 °C  
Tensiune de alimentare - 220-240 V  
Operating temperature - -25 +50 °C  
Frecvenaf nominalaf (Hz) - 50/60 Hz  
MATERIALS - -  
Driver - Included  
Body - Polycarbonate  
Driver failure rate - F10 = 100.000h Tq25°C  
Ecran - UV stabilised polycarbonate  
Overvoltage protection - DM 1KV / CM 2KV  
Optic - Integrated in the screen  
Control System - Through wiring - DALI  
Gasket - CNC deposited sealant  
INSTALLATION AND MAINTENANCE - -  
Locking Hook - -  
Mounting and installation - Ceiling - Wallmounting - Suspension  
External screw - -  
Tilt - With fixing bracket  
Colour - RAL7035 colored PC paste  
Wiring - With GW connect watertight connector  
STANDARDS AND APPROVALS - -  
Prindere - Stainless steel support  
Clasificare - -  
Optic Maintenance - Not available  
Dispozitiv cu temperaturaf la suprafaf redusaf - Da  
LED Maintenance - Not available  
Certificare DIN 18032-3 - Not available  
Driver Box - Integrat  
IPEA - -  
Suprafaf maximaf expusaf la vant - -  
Clasaf izolafie - II  
- - -  
Clasaf de protecafie IP - IP66/IP69  
- - -  
Cod IK - IK08  
- - -  
Glow Test conductori - 850 °C  
- - -  
Ware number - 94051040  
Pret: 884,86 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/corp-de-iluminat-cu-led-liniar-etans-smart-3-plus-1200-difuzor-opal-dali-conector-conexiune-rapida-5-700k-cri-80-216341>