

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**GEWISS CORP DE ILUMINAT CU LED LINIAR ETANS SMART[3] PLUS
- 1200 - INTEGRATED EMERGENCY - DALI DT1 - 3H DT6 - 3000K -
CRI>90**

GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Lighting of warehouses, indoor parking and industrial production rooms
Optic - Microprismatic transparent
Luminaire - LED fixture for general lighting
Unified Glare Rating - UGR \leq 25 (4H/4H)
Aplicatie - Intern
Lumen
output (lm) - 4200 (460 Em.)
Unique digital code (Datamatrix) - Datamatrix
Efficiency
(lm/W) - 98
Culoare - Gri RAL 7035
Culoare Temperatur - 3000 K
Tip sursă de lumină - LED - Neînlocuibil
Color Rendering Index - CRI>90
System
power - 38W (+5W Emerg.)
Standard Deviation Colour Matching - SDCM = 3
LED Lifetime - L90B10(Tq25°C)=50.000h; L80B10(Tq25°C)=100.000h
Photobiological Risk Class - RG0
Greutate (Kg) - 2.8
Standard - EN60598-1; IEC 62778; IEC62471; 60598-2-22
Garanție - 5 ani
ELECTRICAL AND LIGHTING FEATURES - -
Temperatură de stocare - -15°C ÷ +25°C
Tensiune de alimentare - 220 - 240 V
Operating temperature - +5°C ÷ +40 °C
Frecvență nominală (Hz) - 50 / 60
MATERIALS - -
Driver - Included
Body - Polycarbonate
Driver failure rate - F10 = 100.000h Tq25°C
Ecran - UV stabilised polycarbonate
Overvoltage protection - DM 1KV / CM 2KV
Optic - Integrated in the screen
Control System - 1 x DALI DT6 + 1 x DALI DT1 (Emerg. 3h)
Gasket - CNC deposited sealant
INSTALLATION AND MAINTENANCE - -
Locking Hook - -
Mounting and installation - Ceiling - Wallmounting - Suspension
External screw - -
Tilt - With fixing bracket
Colour - RAL7035 colored PC paste
Wiring - With GW connect watertight connector
STANDARDS AND APPROVALS - -
Prindere - Stainless steel support
Clasificare - KITE MARK (Emergency KIT)
Optic Maintenance - Not available
Dispozitiv cu temperatură la suprafață redusă - Da
LED Maintenance - Only for LiFePO battery
Certificare DIN 18032-3 - -
Driver Box - Integrat
IPEA - -
Suprafață maximă expusă la vant - -
Clasă izolație - II
- - -
Clasă de protecție IP - IP65
- - -
Cod IK - IK08
- - -
Glow Test conductori - 850 °C
- - -
Ware number - 94051040
Pret: 1 552,84 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/corp-de-iluminat-cu-led-liniar-etans-smart-3-plus-1200-integrated-emergency-dali-dt1-3h-dt6-3000k-cri-90-216357>