

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**GEWISS CORP DE ILUMINAT CU LED LINIAR ETANS SMART[3] -
DIFUZOR OPAL - STAND ALONE - 1600MM - 4000 K (CRI 80) -
220/240V 50/60HZ - IP66/IP69 - CLASS II**

GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Lighting of warehouses, indoor parking and industrial production rooms
Optic - Wide opal
Luminaire - LED fixture for general lighting
Unified Glare Rating - UGR \leq 25 (4H/8H)
Aplicatie - Intern
Luminanta (lm) - 6400
Unique digital code (Datamatrix) - Datamatrix
Efficiency
(lm/W) - 128
Culoare - Grey (RAL 7035)
Culoare Temperatur - 4000 K
Tip sursa de lumina - LED - Neinlocuibil
Color Rendering Index - CRI > 80
Puterea sistemului - 50 W
Standard Deviation Colour Matching - SDCM = 3
LED Lifetime - L90B10(Tq25°C)=45.000h; L80B10(Tq25°C)=92.000h
Photobiological Risk Class - RG0
Greutate (Kg) - 2.5
Standard - EN60598-1; IEC 62778; IEC62471
Garantie - 5 ani
ELECTRICAL AND LIGHTING FEATURES - -
Temperatur de stocare - -25 +80 °C
Tensiune de alimentare - 220 - 240 V
Operating temperature - -25 +50 °C
Frecventa nominala (Hz) - 50/60 Hz
MATERIALS - -
Driver - Included
Body - Polycarbonate
Driver failure rate - F10 = 100.000h Tq25°C
Ecran - UV stabilised polycarbonate
Overvoltage protection - DM 1KV / CM 2KV
Optic - Integrated in the screen
Control System - Stand Alone - On / Off
Gasket - CNC deposited sealant
INSTALLATION AND MAINTENANCE - -
Locking Hook - -
Mounting and installation - Ceiling - Wallmounting - Suspension
External screw - -
Tilt - With fixing bracket
Colour - RAL7035 colored PC paste
Wiring - With GW connect watertight connector
STANDARDS AND APPROVALS - -
Prindere - Stainless steel support
Clasificare - -
Optic Maintenance - Not available
Dispozitiv cu temperatura la suprafata redus - Da
LED Maintenance - Not available
Certificare DIN 18032-3 - Not available
Driver Box - Integrat
IPEA - -
Suprafata maxima expusa la vant - -
Clasificatie izolare - II
- - -
Clasificatie de protectie IP - IP66/IP69
- - -
Cod IK - IK08
- - -
Glow Test conductori - 850 °C
- - -
Ware number - 94051040
Pret: 542,25 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/corp-de-iluminat-cu-led-liniar-etans-smart-3-difuzor-opal-stand-alone-1600mm-4000-k-cri-80-220-240v-50-60hz-ip66-ip69-class-ii-216386>