

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**GEWISS CORP DE ILUMINAT CU LED LINIAR ETANS SMART[3] PLUS
- 1600 HLO - TRANSPARENT DIFFUSER - ON / OFF - CONECTOR
CONEXIUNE RAPIDA - 3.000K CRI>80**

GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Lighting of warehouses, indoor parking and industrial production rooms
Optic - Microprismatic transparent
Luminaire - LED fixture for general lighting
Unified Glare Rating - UGR \leq 25 (4H/3H)
Aplicatie - Intern
Luminanta (lm) - 8900
Unique digital code (Datamatrix) - Datamatrix
Efficiency
(lm/W) - 146
Culoare - Gri RAL 7035
Culoare Temperaturaf - 3000 K
Tip sursaf de luminaf - LED - Neinlocuibil
Color Rendering Index - CRI>80
Puterea sistemului - 61 W
Standard Deviation Colour Matching - SDCM = 3
LED Lifetime - L90B10(Tq25°C)=50.000h; L80B10(Tq25°C)=100.000h
Photobiological Risk Class - RG0
Greutate (Kg) - 3.8
Standard - EN60598-1; IEC 62778; IEC62471
Garanafie - 5 ani
ELECTRICAL AND LIGHTING FEATURES - -
Temperaturaf de stocare - -25 +80 °C
Tensiune de alimentare - 220-240 V
Operating temperature - -25 +50 °C
Frecvenaf nominalaf (Hz) - 50/60 Hz
MATERIALS - -
Driver - Included
Body - Polycarbonate
Driver failure rate - F10 = 100.000h Tq25°C
Ecran - UV stabilised polycarbonate
Overvoltage protection - DM 1KV / CM 2KV
Optic - Integrated in the screen
Control System - Through wiring - On/Off
Gasket - CNC deposited sealant
INSTALLATION AND MAINTENANCE - -
Locking Hook - -
Mounting and installation - Ceiling - Wallmounting - Suspension
External screw - -
Tilt - With fixing bracket
Colour - RAL7035 colored PC paste
Wiring - With GW connect watertight connector
STANDARDS AND APPROVALS - -
Prindere - Stainless steel support
Clasificare - -
Optic Maintenance - Not available
Dispozitiv cu temperaturaf la suprafaf redusaf - Da
LED Maintenance - Not available
Certificare DIN 18032-3 - Not available
Driver Box - Integrat
IPEA - -
Suprafaf maximaf expusaf la vant - -
Clasaf izolafie - II
- - -
Clasaf de protecáfie IP - IP66/IP69
- - -
Cod IK - IK08
- - -
Glow Test conductori - 850 °C
- - -
Ware number - 94051040
Pret: 806,80 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/corp-de-iluminat-cu-led-liniar-etans-smart-3-plus-1600-hlo-transparent-diffuser-on-off-conector-conexiune-rapida-3-000k-cri-80-216516>