

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**GEWISS CORP DE ILUMINAT CU LED SMART [4] - HE - 1 MODUL -  
STAND ALONE - 1 X DALI DT6 - 30Å° OPTIC - 3000 K - IP66 - CLASS I**

GENERAL INFORMATION - -  
OPTIC AND ILLUMINATING FEATURES - -  
Context - Logistics and industrial manufacturing lighting  
OpticÅf - 30°  
Luminaire - LED Industrial Reflector  
Unified Glare Rating - UGR ≤ 22  
AplicaÅie - InternÅf  
LuminÅf ieÅyire (lm) - 6600  
Unique digital code (Datamatrix) - Datamatrix  
Efficiency  
(lm/W) - 138  
Culoare - Gri RAL 7035  
Culoare TemperaturÅf - 3000 K  
Tip sursÅf de luminÅf - LED - Neinlocuibil  
Color Rendering Index - CRI>80  
Puterea sistemului - 48 W  
Standard Deviation Colour Matching - SDCM = 3  
LED Lifetime - L90B10(Tq25°C)>150.000h; L90B10(Tq50°C)=100.000h  
Photobiological Risk Class - RG0  
Greutate (Kg) - 3.5  
Standard - EN 60598-1 ; EN 60598-2-1 ; EN 60598-2-24  
GaranÅie - 5 ani  
ELETRICAL AND LIGHTING FEATURES - -  
TemperaturÅf de stocare - -40 +70 °C  
Tensiune de alimentare - 220 - 240 V  
Operating temperature - -30°C ÷ +50 °C  
FrecvenÅef nominalÅf (Hz) - 50/60 Hz  
MATERIALS - -  
Driver - Included  
Body - PA6 "Halogen Free" loaded fibreglass  
Driver failure rate - F10=100.000h Tq25°C/50.000h Tq50°C  
Ecran - Tempered glass Thickness 4mm  
Overvoltage protection - DM 6 kV / CM 10 kV  
Optic - Metallic PC reflector and PMMA lenses  
Control System - 1 x DALI DT6  
Gasket - anti-aging silicone  
INSTALLATION AND MAINTENANCE - -  
Locking Hook - -  
Mounting and installation - Ceiling - Wallmounting - Suspension  
External screw - OÅfel  
Tilt - With bracket accessory  
Colour - Gri RAL 7035  
Wiring - With GW connect watertight connector  
STANDARDS AND APPROVALS - -  
Prindere - -  
Clasificare - -  
Optic Maintenance - Non-replaceable  
Dispozitiv cu temperaturÅf la suprafaÅef redusÅf - Da  
LED Maintenance - Non-replaceable  
Certificare DIN 18032-3 - With Bracket - Rope Kit + terminal (in approval)  
Driver Box - Integrat  
IPEA - -  
SuprafaÅef maximÅf expusÅf la vant - 0,097 m²  
ClasÅf izolaÅie - I  
- - -  
ClasÅf de protecÅie IP - IP66  
- - -  
Cod IK - IK08  
- - -  
Glow Test conductori - 850 °C  
- - -  
Ware number - 94051098  
Pret: 1 259,88 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/corp-de-iluminat-cu-led-smart-4-he-1-modul-stand-alone-1-x-dali-dt6-300-optic-3000-k-ip66-class-i-216704>