

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**GEWISS CORP DE ILUMINAT CU LED SMART [4] - HACCP - 1 MODUL
- STAND ALONE - 1 X DALI DT6 - 90° OPTIC - 5700 K - IP65 - CLASS I**

GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Lighting of logistical and industrial food productive premises
Optic - 90°
Luminaire - LED Industrial Reflector
Unified Glare Rating - UGR ≤ 25
Aplicatie - Intern
Luminance (lm) - 9200
Unique digital code (Datamatrix) - Datamatrix
Efficiency
(lm/W) - 144
Culoare - Gri RAL 7035
Culoare Temperatur - 5700 K
Tip sursă de lumină - LED - Neînlocuibil
Color Rendering Index - CRI>80
Puterea sistemului - 64 W
Standard Deviation Colour Matching - SDCM = 3
LED Lifetime - L90B10(Tq25°C)>150.000h; L90B10(Tq50°C)=100.000h
Photobiological Risk Class - RG0
Greutate (Kg) - 3.5
Standard - EN 60598-1 ; EN 60598-2-1 ; EN 60598-2-24
Garanție - 5 ani
ELECTRICAL AND LIGHTING FEATURES - -
Temperatură de stocare - -40 +70 °C
Tensiune de alimentare - 220 - 240 V
Operating temperature - -30 +50 °C
Frecvență nominală (Hz) - 50/60 Hz
MATERIALS - -
Driver - Included
Body - PA6 "Halogen Free" loaded fibreglass
Driver failure rate - F10=100.000h Tq25°C/50.000h Tq50°C
Ecran - PMMA
Overvoltage protection - DM 6 kV / CM 10 kV
Optic - Metallic PC reflector and PMMA lenses
Control System - 1 x DALI DT6
Gasket - anti-aging silicone
INSTALLATION AND MAINTENANCE - -
Locking Hook - -
Mounting and installation - Ceiling - Wallmounting - Suspension
External screw - Oțel
Tilt - With bracket accessory
Colour - Gri RAL 7035
Wiring - With GW connect watertight connector
STANDARDS AND APPROVALS - -
Prindere - -
Clasificare - -
Optic Maintenance - Non-replaceable
Dispozitiv cu temperatură la suprafață redusă - Da
LED Maintenance - Non-replaceable
Certificare DIN 18032-3 - -
Driver Box - Integrat
IPEA - -
Suprafață maximă expusă la vant - 0,097 m²
Clasă izolație - I
- - -
Clasă de protecție IP - IP65
- - -
Cod IK - IK07
- - -
Glow Test conductori - 650 °C
- - -
Ware number - 94051098
Pret: 1 259,14 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/corp-de-iluminat-cu-led-smart-4-haccp-1-modul-stand-alone-1-x-dali-dt6-900-optic-5700-k-ip65-class-i-216743>