

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**GEWISS CORP DE ILUMINAT CU LED SMART [4] - HLO - 1 MODUL -  
EMERGENCY - 1 X DALI DT6 + 1 X DALI DT1 (EMERG. 3H) - 60°  
OPTIC - 5700 K - IP65 - CLASS I**

GENERAL INFORMATION - -  
OPTIC AND ILLUMINATING FEATURES - -  
Context - Logistics and industrial manufacturing lighting  
Optic - 60°  
Luminaire - LED Industrial Reflector  
Unified Glare Rating - UGR ≤ 25  
Aplicatie - Intern  
Lumen  
output (lm) - 9200 (850 Emerg.)  
Unique digital code (Datamatrix) - Datamatrix  
Efficiency  
(lm/W) - 133  
Culoare - Gri RAL 7035  
Culoare Temperatur - 5700 K  
Tip sursă de lumină - LED - Neînlocuibil  
Color Rendering Index - CRI>80  
System  
power - 64 W (+5W Emerg.)  
Standard Deviation Colour Matching - SDCM = 3  
LED Lifetime - L90B10(Tq25°C)>150.000h; L90B10(Tq40°C)=140.000h  
Photobiological Risk Class - RG0  
Greutate (Kg) - 5  
Standard - EN 60598-2-22 ; EN 60598-1 ; EN 60598-2-24  
Garanție - 5 ani  
ELECTRICAL AND LIGHTING FEATURES - -  
Temperatură de stocare - -40 +70 °C  
Tensiune de alimentare - 220 - 240 V  
Operating temperature - 0 ÷ +40 °C  
Frecvență nominală (Hz) - 50/60 Hz  
MATERIALS - -  
Driver - Included  
Body - PA6 "Halogen Free" loaded fibreglass  
Driver failure rate - F10 = 100.000h Tq25°C/50.000h Tq40°C  
Ecran - Tempered glass Thickness 4mm  
Overvoltage protection - DM 6 kV / CM 10 kV  
Optic - Metallic PC reflector and PMMA lenses  
Control System - 1 x DALI DT6 + 1 x DALI DT1 (Emerg. 3h)  
Gasket - anti-aging silicone  
INSTALLATION AND MAINTENANCE - -  
Locking Hook - -  
Mounting and installation - Ceiling light - Suspension  
External screw - Oțel  
Tilt - -  
Colour - Gri RAL 7035  
Wiring - With GW connect watertight connector  
STANDARDS AND APPROVALS - -  
Prindere - -  
Clasificare - -  
Optic Maintenance - Non-replaceable  
Dispozitiv cu temperatură la suprafață redusă - Da  
LED Maintenance - NiMh Battery Only  
Certificare DIN 18032-3 - -  
Driver Box - Integrat  
IPEA - -  
Suprafață maximă expusă la vant - 0,140 m²  
Clasă izolație - I  
- - -  
Clasă de protecție IP - IP65  
- - -  
Cod IK - IK08  
- - -  
Glow Test conductori - 850 °C  
- - -  
Ware number - 94051098  
Pret: 2 606,29 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/corp-de-iluminat-cu-led-smart-4-hlo-1-modul-emergency-1-x-dali-dt6-1-x-dali-dt1-emerg-3h-600-optic-5700-k-ip65-class-i-216847>