

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**GEWISS CORP DE ILUMINAT CU LED SMART [4] - UL -2 MODULE -
STAND ALONE - ON / OFF - 90° OPTIC - 5700 K - IP66 - CLASS I**

GENERAL INFORMATION - -
OPTIC AND ILLUMINATING FEATURES - -
Context - Logistics and industrial manufacturing lighting
Optic - 90°
Luminaire - LED Industrial Reflector
Unified Glare Rating - UGR ≤ 25
Aplicatie - Intern
Luminanta (lm) - 17800
Unique digital code (Datamatrix) - Datamatrix
Efficiency
(lm/W) - 138
Culoare - Gri RAL 7035
Culoare Temperatur - 5700 K
Tip sursa de luminanta - LED - Neinlocuibil
Color Rendering Index - CRI>80
Puterea sistemului - 129 W
Standard Deviation Colour Matching - SDCM = 3
LED Lifetime - L90B10(Tq25°C)>150.000h; L90B10(Tq40°C)=140.000h
Photobiological Risk Class - RG0
Greutate (Kg) - 6.5
Standard - UL 1598 - CSA C22.2 No. 250.0-18
Garanatie - 5 ani
ELECTRICAL AND LIGHTING FEATURES - -
Temperatur de stocare - -
Tensiune de alimentare - 120-277 V
Operating temperature - -25°C ÷ +40 °C
Frecventa nominala (Hz) - 50/60 Hz
MATERIALS - -
Driver - Included
Body - PA6 "Halogen Free" loaded fibreglass
Driver failure rate - F10=100.000h Tq25°C/50.000h Tq40°C
Ecran - Tempered glass Thickness 4mm
Overvoltage protection - DM 6 kV / CM 10 kV
Optic - Metallic PC reflector and PMMA lenses
Control System - ON / OFF
Gasket - anti-aging silicone
INSTALLATION AND MAINTENANCE - -
Locking Hook - -
Mounting and installation - Ceiling - Wallmounting - Suspension
External screw - O-fel
Tilt - With bracket accessory
Colour - Gri RAL 7035
Wiring - Single wiring with anti-breathing cable exiting metallic PG (NO Connector)
STANDARDS AND APPROVALS - -
Prindere - -
Clasificare - -
Optic Maintenance - Non-replaceable
Dispozitiv cu temperatura la suprafata redus - Da
LED Maintenance - Non-replaceable
Certificare DIN 18032-3 - -
Driver Box - Integrat
IPEA - -
Suprafata maxima expusa la vant - 0,184 m²
Clasifica izolatie - I
- - -
Clasifica de protectie IP - IP66
- - -
Cod IK - IK08
- - -
Glow Test conductori - 850 °C
- - -
Ware number - 94051098
Pret: 3 170,03 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/corp-de-iluminat-cu-led-smart-4-ul-2-module-stand-alone-on-off-900-optic-5700-k-ip66-class-i-216977>